

CI/SfB	(31)	Lt3
CAW P10		
Uniclass L681		

Description

ME904 is a solvent free, acrylic copolymer primer.

Colour

White on application, transparent after drying

Packaging

1 litre tins.

Technical Information

Property	Result
Material	Based on polyvinyl acetate - water based system (dispersion)
Drying Time	10 to 40 minutes (depending on porosity/ relative humidity)
Consumption per Litre	Approximately 6-8 m ² (depending on surface)
Storage	Store in shaded dry conditions between +5°C and 30°C
Shelf Life	24 months when stored as recommended in original unopened containers



Protective Equipment

USE IN WELL VENTILATED CONDITIONS and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

Application

- The surface should be dry, and free from dust and grease.
- Remove concrete and cement residues.
- Protect adjacent surfaces with masking tape.
- Apply evenly and carefully onto the surface using a brush.
- After use, ensure the tin is firmly closed.
- Adhesion and drying time is dependent on ambient temperature and humidity.
- If unsure, carry out a preliminary adhesion test.

Cleaning

Splashes should be removed with water.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

ME904

Adhesive Tape Primer

Usage / Purpose

ME904 is used for the pre-treatment of building substrates, e.g. cement particle board, masonry, timber, etc., when using illbruck building protection tapes, particularly for bonding to damp substrates.

Key Benefits

- Optimises adhesion
- Stabilisation of the surface
- Short drying time
- Solvent free
- Allows use of illbruck building protection tapes in damp conditions

Technical Service

tremco CPG UK Ltd has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

tremco CPG UK products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco

CPG UK Ltd written instructions and (b) in any application recommended by tremco CPG UK Ltd, but which is proved to be defective, will be replaced free of charge. No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct. tremco CPG UK Ltd Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



Tremco CPG UK Limited
Coupland Road
Hindley Green, Wigan WN2 4HT
United Kingdom
T: +44 1942 251400
F: +44 1942 251410

info.uk@tremcocpg.com
www.tremcocpg.eu