Page 1/13



Safety data sheet acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 05.09.2021

Version number 9

Revision: 05.09.2021

SECTION 1: Identification of the substance/mixture and of the company undertaking [•] 1.1 Product identifier [•] Trade name: <u>illbruck FM310</u>
· Trade name: <u>illbruck FM310</u>
 MSDS code: A-I-FM310 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. Application of the substance / the mixture Sealant
 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Tremco CPG Netherlands B.V. Vlietskade 1032, 4241 WC Arkel T: +31 (0) 183568000, F: +31 (0) 183568100 msds@cpg-europe.com
 Further information obtainable from: Tremco CPG UK Ltd Coupland Road, Hindley Green, Wigan, WN2 4HT T: +44 (0) 1942251400, F: +44 (0) 1942251410 www.cpg-europe.com, info.uk@cpg-europe.com
 • 1.4 Emergency telephone number: During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 11 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact doctor.
SECTION 2: Hazards identification
 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin Sens. 1 H317 May cause an allergic skin reaction. Carc. 2 H351 Suspected of causing cancer. STOT SE 3 H335 May cause respiratory irritation. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
(Contd. on page



Printing date 05.09.2021

Version number 9

Revision: 05.09.2021

Trade name: illbruck FM310

	(Contd. of page 1)				
 Hazard pictograms 					
$\land \land \land$					
\checkmark \checkmark \checkmark					
GHS02 GHS07 GHS08					
 Signal word Danger 					
· Contains:					
diphenylmethanediisocyanate	e, isomers and homologues				
Hazard statements					
H222-H229 Extremely flamm	able aerosol. Pressurised container: May burst if heated.				
H332 Harmful if inhaled	d.				
H315 Causes skin irrita	ation.				
H319 Causes serious e	e irritation.				
	y or asthma symptoms or breathing difficulties if inhaled.				
	ergic skin reaction.				
H351 Suspected of cau					
H335 May cause respir					
•	ige to organs through prolonged or repeated exposure.				
Precautionary statements					
• •	n heat, hot surfaces, sparks, open flames and other ignition sources. No				
smoking.					
	an open flame or other ignition source.				
P251 Do not pierce or burn, even after use.					
	lust/fume/gas/mist/vapours/spray.				
	quate ventilation wear respiratory protection.				
	espiratory symptoms: Call a POISON CENTER/doctor.				
	light. Do not expose to temperatures exceeding 50 °C/122 °F.				
Supplemental information:	Na Marina dura an allandia na atian				
	es. May produce an allergic reaction.				
•	As from 24 August 2023 adequate training is required before industrial or professional use.				
· 2.3 Other hazards					
• Results of PBT and vPvB as	ssessment				
• PBT: Not applicable.					
· vPvB: Not applicable.					
	en/information on ingradiante				
SECTION 3: Composition	on/information on ingredients				
· 3.2 Mixtures					
· Description: Active substance	ce with propellant				
Dangerous components:					
CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues 30-<50%				
EC number: 618-498-9	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;				
	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;				
	Skin Sens. 1, H317; STOT SE 3, H335				
	(Contd. on page 3)				
	GB				



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 05.09.2021

Version number 9

Revision: 05.09.2021

Trade name: illbruck FM310

		Contd. of page 2)
CAS: 1244733-77-4 EC number: 807-935-0 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chloro-1-methylethyl)phosphate Acute Tox. 4, H302	10-<20%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 9082-00-2	Ethoxylated/propoxylated glycerol Acute Tox. 4, H302	5-<10%
CAS: 25791-96-2 NLP: 500-044-5	Glycerol, propoxylated Acute Tox. 4, H302	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<5%

· SVHC -

• Additional information:

For the wording of the listed hazard phrases refer to section 16.

While curing the following substances are formed and released by a reaction with atmospheric humidity: Carbon dioxide (CO2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information: Take affected persons out of danger area and lay down.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove all soiled and contaminated clothing If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- · Information for doctor: No further relevant information available.

· 4.2 Most important symptoms and effects, both acute and delayed

Harmful if inhaled.

Irritating to eyes, respiratory system and skin.

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 4)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758 Printing date 05.09.2021 Version number 9 Revision: 05.09.2021 Trade name: illbruck FM310 (Contd. of page 3) · Hazards No further relevant information available. · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available. SECTION 5: Firefighting measures 5.1 Extinguishing media Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · For safety reasons unsuitable extinguishing agents: Water with full jet - 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. Carbon monoxide (CO) Carbon dioxide (CO2) Nitrogen oxides (NOx) Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.: Hydrogen cyanide (HCN) 5.3 Advice for firefighters • Protective equipment: Wear self-contained respiratory protective device. SECTION 6: Accidental release measures • 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Avoid contact with the eyes and skin. Ensure adequate ventilation. • 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. · 6.3 Methods and material for containment and cleaning up: Dispose of contaminated material as waste according to Section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. SECTION 7: Handling and storage 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

Avoid contact with the eyes and skin.

Avoid breathing vapours/spray.

Wear suitable protective clothing and gloves.

The usual precautionary measures are to be adhered to when handling chemicals.

(Contd. on page 5)



Printing date 05.09.2021

Version number 9

Revision: 05.09.2021

Trade name: illbruck FM310

(Contd. of page 4)

	(Contd. of page
	nation about fire - and explosion protection:
	nely flammable aerosol.
	irised container: May burst if heated. spray onto a naked flame or any incandescent material.
	t against electrostatic charges.
	urised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.
	c lights. Do not pierce or burn, even after use.
	away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
· 7.2 Co	nditions for safe storage, including any incompatibilities
Storag	
	rements to be met by storerooms and receptacles:
Observ	ve official regulations on storing packagings with pressurised containers.
	nation about storage in one common storage facility: Store away from water.
	er information about storage conditions:
	n cool, dry conditions in well sealed receptacles.
	seal receptacle gas tight. t from heat and direct sunlight.
	ecific end use(s) No further relevant information available.
•	
[.] 8.1 Co	TION 8: Exposure controls/personal protection Introl parameters Innal information about design of technical facilities: No further data: see item 7
· 8.1 Co · Additie	ntrol parameters onal information about design of technical facilities: No further data; see item 7.
· 8.1 Co · Additio · Ingred	ntrol parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace:
• 8.1 Co • Additio • Ingred CAS: 9	ontrol parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues
• 8.1 Co • Additio • Ingred CAS: 9 WEL	ontrol parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³
· 8.1 Co · Additio · Ingred CAS: 9 WEL	ontrol parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³
• 8.1 Co • Additio • Ingred CAS: 9 WEL	ontrol parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
· 8.1 Co · Additio · Ingred CAS: 9 WEL	ontrol parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether
• 8.1 Co • Additio • Ingred CAS: 9 WEL	ontrol parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
• 8.1 Co • Additio • Ingred CAS: 9 WEL	 Introl parameters Information about design of technical facilities: No further data; see item 7. Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit value: 0.07 mg/m³ Long-term value: 0.02 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm
· 8.1 Co · Addition · Ingred CAS: 9 WEL 9 CAS: 1 WEL 9 WEL 9 VEL 9	 Introl parameters Information about design of technical facilities: No further data; see item 7. Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit values that require monitoring at the workplace: Itents with limit value: 0.07 mg/m³ Long-term value: 0.02 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm
• 8.1 Co • Addition • Ingred CAS: 9 WEL • CAS: 1 • WEL • PNEC9 CAS: 9	Introl parameters onal information about design of technical facilities: No further data; see item 7. Itents with limit values that require monitoring at the workplace: 2016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm s
• 8.1 Co • Addition • Ingred CAS: 9 WEL • CAS: 1 • WEL • PNEC9 CAS: 9	Antrol parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm S 0016-87-9 diphenylmethanediisocyanate, isomers and homologues
• 8.1 Co • Addition • Ingred CAS: 9 WEL • CAS: 1 • WEL • PNEC9 CAS: 9	Introl parameters onal information about design of technical facilities: No further data; see item 7. Itents with limit values that require monitoring at the workplace: 2016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm S 2016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release)
· 8.1 Co · Addition · Ingred CAS: 9 WEL CAS: 1 WEL WEL CAS: 9 · PNEC	Introl parameters onal information about design of technical facilities: No further data; see item 7. Iients with limit values that require monitoring at the workplace: 2016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm S 2016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water)
• 8.1 Co • Addition CAS: 9 WEL CAS: 1 WEL WEL WEL NEC CAS: 9 PNEC	Introl parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace: 2016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm S 2016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water) 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate
• 8.1 Co • Addition CAS: 9 WEL CAS: 1 WEL WEL WEL NEC CAS: 9 PNEC	Introl parameters onal information about design of technical facilities: No further data; see item 7. lients with limit values that require monitoring at the workplace: 2016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm S 2016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water) 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate 0.64 mg/L (fresh water)
• 8.1 Co • Addition CAS: 9 WEL CAS: 1 WEL WEL WEL CAS: 1 PNEC	Introl parameters onal information about design of technical facilities: No further data; see item 7. Itients with limit values that require monitoring at the workplace: 2016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm 5 2016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water) 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate 0.64 mg/L (fresh water) 0.064 mg/L (marine)
• 8.1 Co • Addition CAS: 9 WEL CAS: 1 WEL WEL WEL CAS: 1 PNEC	Introl parameters onal information about design of technical facilities: No further data; see item 7. Itients with limit values that require monitoring at the workplace: 2016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm S 2016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water) 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate 0.64 mg/L (fresh water) 0.064 mg/L (marine) 1.7 mg/kg dwt (soil)
• 8.1 Co • Addition CAS: 9 WEL CAS: 1 WEL WEL WEL CAS: 1 PNEC	Introl parameters onal information about design of technical facilities: No further data; see item 7. Itients with limit values that require monitoring at the workplace: 2016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm S 2016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water) 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate 0.64 mg/L (fresh water) 0.064 mg/L (marine)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 05.09.2021

Version number 9

Revision: 05.09.2021

Trade name: illbruck FM310

(Contd. of page 5) CAS: 115-10-6 dimethyl ether PNEC 0.155 mg/L (fresh water) 160 mg/L (sewage treatment plant) 1.549 mg/L (intermittent release) 0.016 mg/L (salt water) PNEC 0.045 mg/kg (soil) 0.069 mg/kg (sediment (salt water)) Additional Occupational Exposure Limit Values for possible hazards during processing: While curing the following substances are formed and released by a reaction with atmospheric humidity: Carbon dioxide (CO2) · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: · General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Ensure that washing facilities are available at the work place. Avoid contact with the eyes and skin. Avoid breathing dust/fume/gas/mist/vapours/spray. **Respiratory protection:** In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. For further guidance, please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide". Protection of hands: Protective gloves • Material of gloves Nitrile rubber. NBR Recommended thickness of the material: ≥ 0.4 mm Butyl rubber, BR Recommended thickness of the material: ≥ 0.7 mm · Penetration time of glove material For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6). (Contd. on page 7)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758 Printing date 05.09.2021 Version number 9 Revision: 05.09.2021 Trade name: illbruck FM310 (Contd. of page 6) • Eye protection: Tightly sealed goggles Body protection: Protective work clothing **SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Aerosol Colour: According to product specification · Odour: Characteristic · Odour threshold: Not determined. Mixture reacts violently with water. · pH-value: • Melting point/freezing point: Not applicable, as aerosol. Undetermined. -97 °C · Flash point: · Flammability (solid, gas): Not applicable. · Decomposition temperature: Not determined. · Auto-ignition temperature: Product is not selfigniting. • Explosive properties: Product is not explosive. However, formation of explosive air/ vapour mixtures are possible. · Explosion limits: Lower: 1.8 Vol % 18.6 Vol % Upper: · Vapour pressure at 20 °C: 5,200 hPa · Density at 20 °C: 0.98 g/cm³ · Relative density Not determined. · Vapour density Not determined. Evaporation rate Not applicable. Solubility in / Miscibility with Immiscible / difficult to mix. water: (Contd. on page 8) - GB



Printing date 05.09.2021	
--------------------------	--

Version number 9

Revision: 05.09.2021

Trade	name:	illbruck	FM310
-------	-------	----------	-------

			(Contd. of pag
Partition	coefficien	t: n-octanol/water: Not determined.	
Viscosity			
Dynami		Not determined.	
Kinema	tic:	Not determined.	
Solvent c			
VOC (E		208.7 g/l	
VOC (E	•	21.29 %	
9.2 Other	informatio	on No further relevant information available.	
SECTIO	N 10: Sta	ability and reactivity	
		further relevant information available.	
10.2 Cher			
		sition / conditions to be avoided:	
		used according to specifications.	
		hazardous reactions No dangerous reactions known. avoid No further relevant information available.	
		materials: No further relevant information available.	
	-	composition products:	
Formation of toxic gases is possible during heating or in case of fire. Carbon monoxide and carbon dioxide			
Nitrogen oxides (NOx) Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:			
	mation or icity	xicological information	
11.1 Infor Acute tox Harmful if	mation or ti city inhaled.	n toxicological effects	
11.1 Infor Acute tox Harmful if LD/LC50	mation or cicity inhaled. values rele	evant for classification:	
11.1 Infor Acute tox Harmful if LD/LC50	mation or cicity inhaled. values rele	evant for classification: henylmethanediisocyanate, isomers and homologues	
11.1 Infor Acute tox Harmful if LD/LC50 CAS: 9010	mation or cicity inhaled. values rele 6-87-9 dip	evant for classification:	
11.1 Infor Acute tox Harmful if LD/LC50 CAS: 901 Oral Dermal	mation or cicity inhaled. values rele 6-87-9 dip LD50 LD50	evant for classification: henylmethanediisocyanate, isomers and homologues >10,000 mg/kg (rat)	
11.1 Infor Acute tox Harmful if LD/LC50 CAS: 901 Oral Dermal Inhalative	mation or cicity inhaled. values rela 6-87-9 dip LD50 LD50 LC50/4 h	evant for classification: henylmethanediisocyanate, isomers and homologues >10,000 mg/kg (rat) >10,000 mg/kg (rabbit)	
11.1 Infor Acute tox Harmful if LD/LC50 CAS: 901 Oral Dermal Inhalative	mation or cicity inhaled. values rela 6-87-9 dip LD50 LD50 LC50/4 h	evant for classification: henylmethanediisocyanate, isomers and homologues >10,000 mg/kg (rat) >10,000 mg/kg (rabbit) 1.5 mg/L (rat)	
11.1 Infor Acute tox Harmful if LD/LC50 CAS: 901 Oral Dermal Inhalative CAS: 124 Oral	mation on icity inhaled. values rel 6-87-9 dip LD50 LD50 LC50/4 h 4733-77-4 LD50	evant for classification: henylmethanediisocyanate, isomers and homologues >10,000 mg/kg (rat) >10,000 mg/kg (rabbit) 1.5 mg/L (rat) tris(2-chloro-1-methylethyl)phosphate	
11.1 Infor Acute tox Harmful if LD/LC50 CAS: 901 Oral Dermal Inhalative CAS: 124 Oral	mation on icity inhaled. values rel 6-87-9 dip LD50 LD50 LC50/4 h 4733-77-4 LD50	evant for classification: henylmethanediisocyanate, isomers and homologues >10,000 mg/kg (rat) >10,000 mg/kg (rabbit) 1.5 mg/L (rat) tris(2-chloro-1-methylethyl)phosphate 632 mg/kg (rat)	
11.1 Infor Acute tox Harmful if LD/LC50 CAS: 901 Oral Dermal Inhalative CAS: 124 Oral CAS: 908	mation or cicity inhaled. values rele 6-87-9 dip LD50 LD50 LC50/4 h 4733-77-4 LD50 2-00-2 Eth	evant for classification: henylmethanediisocyanate, isomers and homologues >10,000 mg/kg (rat) >10,000 mg/kg (rabbit) 1.5 mg/L (rat) tris(2-chloro-1-methylethyl)phosphate 632 mg/kg (rat) noxylated/propoxylated glycerol	



Printing date 05.09.2021

Version number 9

Revision: 05.09.2021

Trade name: illbruck FM310

	(Contd. of page
CAS: 25791-96-2 Glycerol, propoxylated	
Oral LD50 1,999 mg/kg (rat)	
Primary irritant effect:	
• Skin corrosion/irritation Causes skin irritation.	
· Serious eye damage/irritation	
Causes serious eye irritation.	
Respiratory or skin sensitisation	
May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
May cause an allergic skin reaction. • Additional toxicological information:	
· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)	
• Germ cell mutagenicity Based on available data, the classification criteria are not met	
Carcinogenicity	-
Suspected of causing cancer.	
• Reproductive toxicity Based on available data, the classification criteria are not met.	
· STOT-single exposure	
May cause respiratory irritation. • STOT-repeated exposure	
May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard Based on available data, the classification criteria are not met.	
SECTION 12: Ecological information 12.1 Toxicity	
· Aquatic toxicity:	
CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues	
LC0/96 h >1,000 mg/L (brachydanio rerio)	
EC50/24 h >1,000 mg/L (daphnia magna)	
CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate	
LC50/96 h 51 mg/L (pimephales promelas)	
CAS: 9082-00-2 Ethoxylated/propoxylated glycerol	
o (1 1 1)	
CAS: 9082-00-2 Ethoxylated/propoxylated glycerol	
CAS: 9082-00-2 Ethoxylated/propoxylated glycerol LC50/48 h >100 mg/L (brachydanio rerio)	
CAS: 9082-00-2 Ethoxylated/propoxylated glycerolLC50/48 h>100 mg/L (brachydanio rerio)EC50/48 h>100 mg/L (daphnia magna)	
CAS: 9082-00-2 Ethoxylated/propoxylated glycerol LC50/48 h >100 mg/L (brachydanio rerio) EC50/48 h >100 mg/L (daphnia magna) EC50/72 h >1,000 mg/L (scenedesmus capricornutum) • 12.2 Persistence and degradability No further relevant information available. • Other information: The product is not easily biodegradable.	
CAS: 9082-00-2 Ethoxylated/propoxylated glycerol LC50/48 h >100 mg/L (brachydanio rerio) EC50/48 h >100 mg/L (daphnia magna) EC50/72 h >1,000 mg/L (scenedesmus capricornutum) • 12.2 Persistence and degradability No further relevant information available.	

(Contd. on page 10)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 05.09.2021

Version number 9

Revision: 05.09.2021

Trade name: illbruck FM310

(Contd. of page 9)

Ecotoxical effects:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

NOEC/21 d >10 mg/L (daphnia magna)

· Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

• **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Do not pierce or burn, even after use.

· European waste catalogue		
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	
08 05 01*	waste isocyanates	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP7	Carcinogenic	
HP13	Sensitising	

Uncleaned packaging:

• **Recommendation:** Dispose of packaging according to regulations on the disposal of packagings.

14.1 UN-Number		
ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
	1950 AEROSOLS	
IMDG	AEROSOLS	
ΙΑΤΑ	AEROSOLS, flammable	



rinting date 05.09.2021	Version number 9	Revision: 05.09.20
rade name: illbruck FM310		
		(Contd. of page
 14.3 Transport hazard class(es) 		
· ADR		
Class Label	2 5F Gases. 2.1	
· IMDG, IATA		
· Class	2.1	
· Label	2.1	
 14.4 Packing group ADR, IMDG, IATA 	Void	
 14.5 Environmental hazards: Marine pollutant: 	No	
14.6 Special precautions for user	Warning: Gases.	
 Hazard identification number (Kemler c EMS Number: 	ode): - F-D.S-U	
· Stowage Code	SW1 Protected from sou	urces of heat.
	SW22 For AEROSOLS litre: Category A. For above 1 litre: Category	with a maximum capacity of AEROSOLS with a capacity of B. For WASTE AEROSOL
· Segregation Code	litre:	with a maximum capacity of
	Segregation as for cla class 1 except for division For AEROSOLS with a c	
	2.	appropriate subdivision of cla
	For WASTE AEROSOLS Segregation as for the a 2.	S: appropriate subdivision of cla
 14.7 Transport in bulk according to Anr Marpol and the IBC Code 	nex II of Not applicable.	
		(Contd. on page



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 05.09.2021

Version number 9

Revision: 05.09.2021

Trade name: illbruck FM310

	(Contd. of page 11)
1L	
Code: E0	
Not permitted as Excepted Quantity	
2	
D	
1L	
Code: E0	
Not permitted as Excepted Quantity	
UN 1950 AEROSOLS, 2.1	
	Code: E0 Not permitted as Excepted Quantity 2 D 1L Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture "EU-CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1)
 "EU-REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments) COMMISSION REGULATION (EU) 2020/878 of 18 June 2020.
 75/324/EEC relating to aerosol dispensers HSE EH40/2005 Workplace Exposure Limits (as amended) Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)
 "GB-CLP" The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019
 "UK-REACH" The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020
 Directive 2012/18/EU
 Qualifying quantity (feagues) for the application of lower tigs requirements 150 t
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $500\ t$
- National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed. Employment restrictions concerning pregnant and lactating women must be observed.

- · Other regulations, limitations and prohibitive regulations No further relevant information available.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

(Contd. on page 13)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 05.09.2021

Version number 9

Revision: 05.09.2021

Trade name: illbruck FM310

(Contd. of page 12) H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. Department issuing SDS: Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3. Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 * * Data compared to the previous version altered. GB