
# Safety Data Sheet according to



Date Printed: 14/07/2021





Regulation (EC) 'No. 2015/830









## SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

FLOWSEAL PU GLOSS (103) **Revision Date:** 14/07/2021 1.1 **Product Identifier** HARDENER B

Supersedes Date: 21/09/2018 Flowseal PU Gloss (103) **Product Name:** 

Hardener B

47Y0-309R-R00V-P6C6 **UFI Code:** 

Relevant identified uses of the substance or mixture and uses advised against

Coatings and paints, thinners, paint removers. Manual activities involving hand contact. Widespread use leading to inclusion into/onto article (indoor). Hardener for 2 components coatings - Industrial use. For use by appropriately trained applicators. Roller application or brushing. Low energy spreading of coatings. Advised against: Home DIY applications, because of the health hazards and training required.

Details of the supplier of the safety data sheet 1.3

> Flowcrete Polska Sp. z o. o. Manufacturer:

Ul. Marywilska 34 03-228 Warszawa

Polska

Tel: +48 22 879 8907 Fax: +48 22 879 8918 ehs.uk@flowcrete.com www.flowcrete.com.pl/

ehs.uk@flowcrete.com **Datasheet Produced by:** 

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)

Giftinformasjonen: +47 22 59 13 00

## **SECTION 2: Hazard Identification**

## 2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

## **HAZARD STATEMENTS**

Other EU extensions	EUH204
Flammable Liquid, category 3	H226
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Acute Toxicity, Inhalation, category 4	H332

### 2.2 Label elements

## Symbol(s) of Product





## Signal Word

Warning

## Named Chemicals on Label

Ethylbenzene, Xylene, Hexamethylene-1,6-diisocyanate homopolymer

## **HAZARD STATEMENTS**

Other EU extensions Flammable Liquid, category 3	EUH204 H226	Contains isocyanates. May produce an allergic reaction. Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
PRECAUTION PHRASES		
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.

## 2.3 Other hazards

No Information

## Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

## SECTION 3: Composition/Information On Ingredients

#### 3.2 Mixtures

Hazardane	ingradiante
i iazai uvus	ingredients

Date Printed: 14/07/2021

Name According to EEC	EINEC No.	CAS-No.	<u>%</u>	Classifications	
Hexamethylene-1,6- diisocyanate homopolymer	500-060-2	28182-81-2	50 - <75	H317	Skin Sens. 1
2-Methoxy-1- methylethyl-acetate	203-603-9	108-65-6	10 - <25	H226-336	Flam. Liq. 3, STOT SE 3 NE
Xylene	215-535-7	1330-20-7	10 - <25	H226-304-315-332	Acute Tox. 4 Inhalation, Asp. Tox. 1, Flam. Liq. 3, Skin Irrit. 2
Ethylbenzene	202-849-4	100-41-4	2.5 - <10	H225-304-332-373-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Flam. Liq. 2, STOT RE 2

CAS-No.	M-Factors	REACH Reg No.
28182-81-2		01-2119488934-20
108-65-6		01-2119475791-29
1330-20-7		01-2119488216-32
100-41-4		01-2119489370-35

Additional Information:

The text for CLP Hazard Statements shown above (if any) is given in Section 16.

## **SECTION 4: First-aid Measures**

#### 4.1 Description of First Aid Measures

**GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance. Risk of product entering the lungs on vomiting after ingestion. Remove contaminated clothing and shoes

**AFTER INHALATION:** Move to fresh air. Consult a physician after significant exposure. Keep respiratory tract clear. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Keep eye wide open while rinsing. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. If swallowed, seek medical advice immediately and show this container or label.

## Self protection of the first aider:

Date Printed: 14/07/2021

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

No Information

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

## **SECTION 5: Fire-fighting Measures**

#### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

#### 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

Keep containers and surroundings cool with water spray. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Fire will produce dense black smoke containing hazardous combustion products (see section 10). Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### **SECTION 6: Accidental Release Measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak. Remove all sources of ignition.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Keep the container open. May cause long-term adverse effects in the aquatic environment.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Refer to protective measures listed in sections 7 and 8.

#### 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## **SECTION 7: Handling and Storage**

## 7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good industrial hygiene and safety practice. Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Wash hands and face before breaks and immediately after handling the product.

## 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Direct sources of heat.

**STORAGE CONDITIONS:** Do not freeze. Store in original container. Store at room temperature in the original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

Component of a resin flooring product. The mixing and application to be in accordance with the technical data sheets.

## **SECTION 8: Exposure Controls/Personal Protection**

## 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
Hexamethylene-1,6-diisocyanate homopolymer	28182-81-2			0.07	0.02
2-Methoxy-1-methylethyl-acetate	108-65-6	50	100	548	274
Xylene	1330-20-7	50	100	441	220
Ethylbenzene	100-41-4	100	125	552	441

Name	CAS-No.	OEL Note
Hexamethylene-1,6-diisocyanate homopolymer	28182-81-2	
2-Methoxy-1-methylethyl-acetate	108-65-6	Can be absorbed through the skin.
Xylene	1330-20-7	Can be absorbed through the skin.
Ethylbenzene	100-41-4	Can be absorbed through the skin.

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

#### 8.2 Exposure controls

#### **Personal Protection**

**RESPIRATORY PROTECTION:** In case of insufficient ventilation wear suitable respiratory equipment. Respirator with a vapor filter. Respirator with filter for organic vapor.

EYE PROTECTION: Eye wash bottle with pure water. Tightly fitting safety goggles. Face-shield.

**HAND PROTECTION:** Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** As a rule, at least 5 air changes per hour are recommended at the workplace. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

# Chemical Name:

Date Printed: 14/07/2021

Hexamethylene-1,6-diisocyanate homopolymer

**EC No.: CAS-No.:** 500-060-2 28182-81-2

## **DNELs - Derived no effect level**

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							
Inhalation	1 mg/m³		0.5 mg/m <sup>3</sup>					
Dermal								

## PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.199 mg/l
Fresh water sediments	44551 mg/kg
Marine water	0.0199 mg/l
Marine sediments	4455 mg/kg
Food chain	
Microorganisms in sewage treatment	100 mg/l
soil (agricultural)	8884 mg/kg
Air	

## **Chemical Name:**

2-Methoxy-1-methylethyl-acetate

**EC No.: CAS-No.:** 203-603-9 108-65-6

## **DNELs - Derived no effect level**

		Wo	orkers			Con	sumers	
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							1.67 mg/kg bw/d
Inhalation				275 mg/m <sup>3</sup>				33 mg/m³
Dermal			153.5 mg/kg bw/				54.8 mg/kg bw/d	
				d				

## PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.635 mg/l
Fresh water sediments	3.29 mg/kg
Marine water	0.0635 mg/l
Marine sediments	0.329 mg/kg
Food chain	
Microorganisms in sewage treatment	100 mg/l
soil (agricultural)	0.29 mg/kg
Air	

## **Chemical Name:**

Date Printed: 14/07/2021

Xylene

**EC No.: CAS-No.:** 215-535-7 1330-20-7

#### **DNELs - Derived no effect level**

		Wo	rkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							1.6 mg/kg
Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	77 mg/m³	174 mg/m <sup>3</sup>	174 mg/m <sup>3</sup>		14.8 mg/m³
Dermal	174 mg/m³	_	·					108 mg/kg

#### PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/l
Fresh water sediments	12.46 mg/kg
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	6.58 mg/l
soil (agricultural)	2.31 mg/kg
Air	

## **SECTION 9: Physical and Chemical Properties**

9.1 Information on basic physical and chemical properties

Appearance: Yellow
Physical State Liquid
Odor Solvent

Odor threshold

PH

Not determined

Melting point / freezing point (°C)

Not determined

Not determined

Not determined

Not determined

Not determined

Not determined

Flash Point, (°C) ca. 38 °C DIN 53213

Evaporation rate Not determined Flammability (solid, gas) Not determined

Upper/lower flammability or explosive No limits

.....

Not determined

Vapour Pressure Not determined Vapour density Not determined

Relative density ca. 1.07

Decomposition temperature (°C)

Solubility in / Miscibility with water Immiscible

Partition coefficient: n-octanol/water Not determined

Auto-ignition temperature (°C) Not determined

Viscosity Not determined

Not determined

Not determined

**Explosive properties** 

Oxidising properties Not determined

9.2 Other information

VOC Content g/l: <500

Specific Gravity (g/cm3) 0.120

## **SECTION 10: Stability and Reactivity**

#### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under recommended storage conditions. No decomposition if stored and applied as directed. Container can be pressurized by carbon dioxide due to reaction with humid air and/or water. Risk of ignition. Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Direct sources of heat.

#### 10.5 Incompatible materials

Acids. Strong oxidizing agents.

## 10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

## **SECTION 11: Toxicological Information**

## 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: No Information Inhalation LC50: No Information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
28182-81-2	Hexamethylene-1,6- diisocyanate homopolymer	> 2500 mg/kg (rat)	> 2001 mg/kg (rat)	18500 mg/kg		
108-65-6	2-Methoxy-1-methylethyl- acetate	8532 mg/kg (rat)	>5000 mg/kg (rat)	1105 mg/m³, 4hr	0.000	0.000
1330-20-7	Xylene	4000 mg/kg (rat)	> 4350 mg/kg (rabbit)		6700	29.08 mg/l (Rat)
100-41-4	Ethylbenzene	3500 mg/kg (rat)	15400 mg/kg, rabbit		0.000	17.2 mg/l (Rat)

#### Additional Information:

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Corrosive - causes irreversible eye damage.

## **SECTION 12: Ecological Information**

### 12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

**12.6 Other adverse effects:** No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
28182-81-2	Hexamethylene-1,6-diisocyanate homopolymer	> 100 mg/l	> 1000 mg/l	> 100 mg/l (danio rerio)
108-65-6	2-Methoxy-1-methylethyl-acetate	500 mg/l	No information	161 mg/l (Pimephales promelas)
1330-20-7	Xylene	1 mg/l	No information	13.4 mg/l (pimephales promelas)
100-41-4	Ethylbenzene	1.8 mg/l	4.6 mg/l	4.2 mg/l (Oncorhynchus mykiss)

## **SECTION 13: Disposal Considerations**

WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. Dispose of as hazardous waste in compliance with local and national regulations. If recycling is not practicable, dispose of in compliance with local regulations. Container hazardous when empty. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

**European Waste Code:** 080501\* **Packaging Waste Code:** 150110

Product: FLOWSEAL PU GLOSS (103) HARDENER B

**SECTION 14: Transport Information** 

Date Printed: 14/07/2021

UN1866 14.1 UN number

14.2 UN proper shipping name Resin solution Not applicable **Technical name** 

14.3 Transport hazard class(es)

Not applicable Subsidiary shipping hazard

14.4 Packing group

Not applicable 14.5 Environmental hazards 14.6 Special precautions for user Not applicable EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

## **SECTION 15: Regulatory Information**

## 15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

**National Regulations:** 

**Denmark Product Registration Number:** Not available

3-3 Danish MAL Code:

Danish MAL Code - Mixture: Not available

**Sweden Product Registration Number:** Not available

170166 **Norway Product Registration Number:** 

**Germany WGK Class:** Not available

Directive 2004/42/CE: <500

Not applicable Covered by Directive 2012/18/EC (Seveso III):

Restrictions to product or to substances according

to Annex XVII, Regulation (CE) 1907/2006: Not applicable

Annex XIV - Authorisation List:

Name According to EEC CAS-No.

Not Applicable

SVHC - Substances of very high concern (Candidate List):

Name According to EEC CAS-No.

Not Applicable

#### 15.2 **Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: Other Information

## Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

May cause an allergic skin reaction. H317

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects. H412

#### Reasons for revision

Date Printed: 14/07/2021

Substance and/or Product Properties Changed in Section(s):

01 - Identification

02 - Hazard Identification

08 - Exposure Controls/Personal Protection

11 - Toxicological Information 12 - Ecological Information 15 - Regulatory Information

Substance Hazard Threshold % Changed

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

#### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

ЕC European Commission European Union ΕU United States US

Chemical Abstract Service CAS

European Inventory of Existing Chemical Substances EINECS

Registration, Evaluation, Authorization of Chemicals Regulation REACH

Globally Harmonized System of Classification and Labeling of Chemicals GHS

LTEL Long term exposure limit STEL Short term exposure limit Occupational exposure limit OEL

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

American Conference of Governmental Industrial Hygienists ACGTH

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits VOC Volatile organic compounds

g/1 Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.