

Date Printed: 19/01/2017

Safety Data Sheet according to Regulation (EC) No. 2015/830

SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier FLOWFRESH/FLOWCRETE Revision Date: 19/01/2017 COATING FILLER C

Product Name: Flowfresh/Flowcrete Coating Filler Supercedes Date: 28/05/2015

C

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Coatings and paints, thinners, paint removers. Hand-mixing with intimate contact and only PPE available. Wide dispersive indoor use resulting in inclusion into or onto a matrix. For use by appropriately trained applicators. This component does NOT contain an antimicrobial agent. Roller application or brushing. Low energy spreading of coatings. Advised against: Any other use.

1.3 Details of the supplier of the safety data sheet

Supplier: Flowcrete UK Ltd.

The Flooring Technology Centre

Booth Lane

Moston, Sandbach, Cheshire. UK

CW11 3QF

Tel: +44 (0)1270 753000 Fax: +44 (0)1270 753333 ehs.uk@flowcrete.com http://www.flowcrete.co.uk

Datasheet Produced by: ehs.uk@flowcrete.com

1.4 Emergency telephone number: CHEMTREC +001 703 5273887 (Outside US)

CHEMTREC 1-800-424-9300 (Inside US)

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Skin Irritation, category 2H315Skin Sensitizer, category 1H317Serious Eye Damage, category 1H318STOT, single exposure, category 3, RTIH335

Date Printed: 19/01/2017

Label elements

Symbol(s) of Product



Signal Word

Danger

2.2

Named Chemicals on Label

Calcium dihydroxide, Cement, portland, chemicals

HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.

PRECAUTION PHRASES

P261	Avoid breathing dust/tume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/
	face protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or
	doctor/physician.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do so.

Continue rinsing.

P333+313 If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

SECTION 3: Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.	EINEC No.	Name According to EEC	<u>%</u>
65997-15-1	266-043-4	Cement, portland, chemicals	75-100
1305-62-0	215-137-3	Calcium dihydroxide	10-25

 CAS-No.
 REACH Reg No.
 CLP Symbols
 CLP Hazard Statements
 M-Factors

 65997-15-1
 GHS05-GHS07
 H315-317-318-335

1305-62-0 01-2119475151-45 GHS05-GHS07 H315-318-335

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

Date Printed: 19/01/2017

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off with soap and plenty of water.

AFTER EYE CONTACT: Keep eye wide open while rinsing. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Not combustible. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Pick up and transfer to properly labelled containers. No special environmental precautions required. After cleaning, flush away traces with water. Refer to protective measures listed in sections 7 and 8.

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Wear personal protective equipment. Avoid dust formation. Protect from moisture.

Date Printed: 19/01/2017 Product: FLOWFRESH/FLOWCRETE COATING FILLER C

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid moisture.

STORAGE CONDITIONS: Keep tightly closed in a dry and cool place.

7.3 Specific end use(s)

Filler C - Flowfresh Cove Coating + Flowcrete Cove Coating. Component of a resin flooring product. The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
Cement, portland, chemicals	65997-15-1				4 10
Calcium dihydroxide	1305-62-0				5

<u>Name</u> CAS-No. OEL Note

Respirable Dust, Cement, portland, chemicals 65997-15-1

Total Inhalable

Calcium dihydroxide 1305-62-0

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Effective dust mask.

EYE PROTECTION: Eye wash bottle with pure water. Safety glasses with side-shields conforming to EN166.

HAND PROTECTION: Protective gloves. Long sleeved clothing. Remove contaminated clothing and protective equipment before entering eating areas.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: As a rule, at least 5 air changes per hour are recommended at the workplace. Ensure adequate ventilation, especially in confined areas.

Date Printed: 19/01/2017

Chemical Name:

EC No.: CAS-No.:

DNELs - Derived no effect level

		Wo	rkers			Con	sumers	
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not	required					
Inhalation								
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical propert
--

Appearance: powder

Physical State Solid

Odor odorless

Odor threshold Not determined

pH ca. 12

Boiling point/range (°C)

Flash Point, (°C)

Evaporation rate

Not determined

Flammability (solid, gas)

Not determined

Upper/lower flammability or explosive

Melting point / freezing point (°C)

limits

999 - 0

Not determined

Vapour Pressure Not determined
Vapour density Not determined

Relative density ca. 2.7

Solubility in / Miscibility with water slight

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Not determined

Not determined

Viscosity

Not determined

Not determined

Not Applicable

Oxidising properties

Not Applicable

9.2 Other information

Date Printed: 19/01/2017

VOC Content g/l: <20

This is a calculated maximum VOC content for the mixed ready to use product (to Directive 2004/42/EC).

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Avoid moisture.

10.5 Incompatible materials

Do not store near acids.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No Information Inhalation LC50: No Information

Irritation: No information available.

Corrosivity: Cement and hydrated lime powder, especially in a water mix, may cause irritant contact

dermatitis and/or burns.

Sensitization: Prolonged or repeated skin contact may result in allergic eczema.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.

Data on individual components are tabulated below:

CAS-No. Name According to EEC Oral LD50 Dermal LD50 Vapor LC50

1305-62-0 Calcium dihydroxide 7340 mg/kg (rat) >2500 mg/kg (rabbit)

Additional Information:

Date Printed: 19/01/2017

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Social Dialogue on Respirable Crystalline Silica and Good Practices Guide

A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide, are available from http://www.nepsi.eu and provide useful information and guidance for the handling of products containing respirable crystalline silica. Literature references are available on request from EUROSIL, the European Association of Industrial Silica Producers.

`Literature References

Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003).

So there is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required.

'Health & Safety Executive (specific for UK):

Detailed reviews of the scientific evidence on the health effects of crystalline silica have been published by HSE (Health and Safety Executive, UK) in the Hazard Assessment Documents EH75/4 (2002) and EH75/5 (2003). The HSE points out on its website that "Workers exposed to fine dust containing quartz are at risk of developing a chronic and possibly severely disabling lung disease known as "silicosis". In addition to silicosis, there is now evidence that heavy and prolonged workplace exposure to dust containing crystalline silica can lead to an increased risk of lung cancer. The evidence suggests that an increased risk of lung cancer is likely to occur only in those workers who have developed silicosis.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: Mostly nonbiodegradable. The hydrated lime will react with atmospheric and

dissolved carbon dioxide to form calcium carbonate (e.g. chalk).

12.3 Bioaccumulative potential: The product is not volatile and insoluble in water, will accumulate in the ground.

12.4 Mobility in soil:No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects:

Date Printed: 19/01/2017

The addition of cement and hydrated lime to water will raise pH and may therefore be toxic to aquatic life in some circumstances.

CAS-No. Name According to EEC EC50 48hr IC50 72hr LC50 96hr

65997-15-1 Cement, portland, chemicals No information No information

1305-62-0 Calcium dihydroxide 49.1 mg/l No information 50.6 mg/l

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 101304 Packaging Waste Code: 150101

SECTION 14: Transport Information

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport according to ADR/RID, IMDG, and IATA

regulations.

Technical name
Not applicable

14.3 Transport hazard class(es)
Subsidiary shipping hazard

Not applicable
Not applicable
Not applicable
Not applicable

14.4 Packing group
Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

according to Annex II Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

WGK Class:

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Date Printed: 19/01/2017

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Reasons for revision

Substance and/or Product Properties Changed in Section(s): 08 - Exposure Controls/Personal Protection Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

Product: FLOWFRESH/FLOWCRETE COATING FILLER C

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

Date Printed: 19/01/2017

IMDG International Maritime Dangerous Goods Code IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

Product: FLOWFRESH/FLOWCRETE COATING FILLER C

Date Printed: 19/01/2017