

illbruck making it perfect.

Description

AA301 is a spray applied product designed to ensure the optimum finish to illbruck sealants.

Packaging

750 ml spray bottles (12 per box)

Protective Equipment

Use in well ventilated conditions and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

Application

- Spray AA301 onto the sealant as soon as possible and before the sealant has started to skin over.
- Avoid applying by brush which can leave tracks in the sealant.
 An alternative method is to dip the smoothing tools into the AA301.
- Tool off as necessary with AA311 Smoothing Tools or similar.
- AA301 is supplied in correct formulation for the most efficient tooling off and no addition of water is necessary.

Use on Natural Stone

- AA301 is suitable for use on natural stone. Use as much as
 necessary but as little as possible. Excess smoothing agent left
 unattended can cause streaks/runs. Remove streaks/runs with
 clean water immediately. Smoothing agent allowed to dry out on
 the stone surface can leave a mark in some circumstances.
- Due to the many types and variations in natural stone, a preliminary test is recommended

Storage

Store in dry, cool conditions away from frost.

Shelf Life

12 months when stored as recommended in original unopened packaging.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



AA301

Silicone Smoothing Agent

Usage / Purpose

AA301 Smoothing Agent is specifically designed for finishing/tooling of illbruck sealants. It can be sprayed on or smoothing tools can be dipped into it. Dilution with water is not required.

Key Benefits

- pH neutral
- Low odour
- Ensures an excellent smooth finish to cured sealants



Tremco CPG UK Limited
Coupland Road
Hindley Green, WIgan WN2 4HT
United Kingdom
T: +44 1942 251400
F: +44 1942 251410

info.uk@tremcocpg.com www.tremcocpg.eu