

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

No. FS709 – 20170519

1. **Unique identification code of the product-type:** Nullifire FS709 Intumastic HP
2. **Intended use/es:** An acrylic based graphite sealant used to reinstate the fire resistance performance of wall and floor constructions where they have been provided with apertures for the penetration of single or multiple services.
3. **Manufacturer:** TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan, UK, WN2 4HT
5. **System/s of AVCP:** System 1
- 6b. **European Assessment Document:** ETAG 026, edition 2011  
used as European Assessment Document  
**European Technical Assessment:** ETA 17/0388  
**Technical Assessment Body:** CPR Notified Body UL International (UK) Ltd, No. 0843  
**Notified Body:** CPR Notified Body UL International (UK) Ltd, No. 0843
7. **Declared performance/s:**

Essential Characteristic	Performance	Harmonised Technical Specification
<b>Safety in Case of Fire</b>		
Reaction to fire	Class E	EN13501-1
Resistance to fire	See ETA 17/0388 Annex A	Classified in accordance with EN 13501-2, as given in Annex A
<b>Hygiene, Health and Environment</b>		
Air permeability	NPD	EN 1026:2000
Release of Dangerous Substances	Use categories: IA3, S/W3 Declaration of manufacturer	Declaration of manufacturer
Water Permeability	NPD	ETAG 026- Annex C
<b>Safety in use</b>		
Mechanical Resistance and stability	NPD	EOTA TR001:2003
Resistance to Impact / movement	NPD	EOTA TR001:2003
Adhesion	NPD	EOTA TR001:2003
<b>Protection against noise</b>		
Airborne Sound Insulation	NPD	EN 10140-2/ EN ISO 717-1
<b>Energy economy and heat retention</b>		
Thermal properties	NPD	EN 12664, EN 12667 or EN 12939

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

Water vapour permeability	NPD	EN ISO 12572 EN 12086
Durability and serviceability	Z <sub>1</sub>	EN 13162 or EN 14303, EN ISO 1519

NPD = No Performance Determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

**Signed for and on behalf of the manufacturer by:**

M. Liptrot, Operations Director  
At Wigan on 1 July 2020



**Annex:**

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

<b>CE</b>	
TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 17 0843-CPR-0380 FS709 – 20170519 www.nullifire.com/FS709	
EN 1366-3: 2009 ETA 17/0388 ETAG 026, Part 2 An acrylic based graphite sealant used to reinstate the fire resistance performance of wall and floor constructions where they have been provided with apertures for the penetration of single or multiple services.	
<b>Essential Characteristic</b>	<b>Performance</b>
<b>Safety in Case of Fire</b>	
Reaction to fire	Class E
Resistance to fire	See ETA 17/0388 Annex A
<b>Hygiene, Health and Environment</b>	
Air permeability	NPD
Dangerous Substances	Use categories: IA3, S/W3 Declaration of manufacturer
<b>Safety in use</b>	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
<b>Protection against noise</b>	
Airborne sound insulation	NPD
<b>Energy, Economy and Heat Retention</b>	
Thermal properties	NPD
Water vapour permeability	NPD
<b>General aspects relating to fitness for use</b>	
Service & Durability	Z <sub>1</sub>