## **illbruck**

# Safety data sheet acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

Trade name: illbruck ME901

· MSDS code: B-I-ME901

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Priming

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Tremco CPG Germany GmbH

Werner-Haepp-Straße 1, D - 92439 Bodenwöhr

T: +49 (0) 9434 2080, F: +49 (0) 9434 208230

msds@cpg-europe.com

#### · Further information obtainable from:

Tremco CPG UK Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.cpg-europe.com, info.uk@cpg-europe.com

#### · 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

#### **SECTION 2: Hazards identification**

## · 2.1 Classification of the substance or mixture

## · Classification according to Regulation (EC) No 1272/2008

Flam. Lig. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aguatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### · 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms









GHS02 GHS07 GHS08 GHS09

(Contd. on page 2)



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

(Contd. of page 1)

## · Signal word Danger

## · Contains:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

butanone

#### Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapours.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Supplemental information:

Restricted to professional users.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

## · 3.2 Mixtures

Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:			
EC number: 927-510-4 Reg.nr.: 01-2119475515-33-xxxx	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	30-<50%	
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%	
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-xxxx	Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	1-<5%	

· SVHC -

• Additional information: For the wording of the listed hazard phrases refer to section 16.

- GB

## **illbruck**

# Safety data sheet acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

(Contd. of page 2)

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

- · Information for doctor: No further relevant information available.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

- 5.3 Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

(Contd. on page 4)



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

(Contd. of page 3)

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace
--

## CAS: 78-93-3 butanone WEL | Short-term value: 899 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics

OES | Long-term value: 600 mg/m³

· PNECs

**CAS: 78-93-3 butanone** 

PNEC 55.8 mg/L (fresh water)

709 mg/L (sewage treatment plant)

55.8 mg/L (sporadic release)

55.8 mg/L (salt water)

PNEC 22.5 mg/kg (soil)

284.7 mg/kg (sediment (salt water))

(Contd. on page 5)



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

(Contd. of page 4)

284.7 mg/kg (sediment (fresh water))

Ingredients with biological limit values:

CAS: 78-93-3 butanone

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Parameter: butan-2-one

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

· Protection of hands:



Protective gloves

Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.4 mm

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Neoprene gloves

· Eye protection:



Tightly sealed goggles



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

(Contd. of page 5)

· Body protection:



Protective work clothing

• 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

• **pH-value:** Mixture is non-polar/aprotic.

• Melting point/freezing point: Undetermined. • Initial boiling point and boiling range: 79-80.5 °C

· Flash point: -1 °C

Flammability (solid, gas): Highly flammable.

· Ignition temperature: >200 °C

• **Decomposition temperature:** Not determined.

• **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

**Lower:** 0.9 Vol % **Upper:** 11.5 Vol %

· Vapour pressure at 20 °C: 16.3 hPa

Density at 20 °C: 0.83 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Fully miscible.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic at 20 °C:** 650 mPas

(Contd. on page 7)



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

	(Contd. of page 6)
Not determined.	
52.01 %	
431.7 g/l	
52.00 %	
0.0 %	
Other information No further relevant information available.	
	52.01 % 431.7 g/l 52.00 % 0.0 %

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions Violent reactions with strong alkalis and oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:			
Hydrocarl	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics			
Oral	LD50	>10,000 mg/kg (rat)		
Dermal	LD50	>3,000 mg/kg (rat)		
Inhalative	LC50/4 h	21 mg/L (rat)		
CAS: 78-93-3 butanone				
Oral	LD50	3,300 mg/kg (rat)		
Dermal	LD50	5,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	34 mg/L (rat)		
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics				
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	3,400 mg/kg (rabbit)		
Inhalative	LC50/4 h	13.1 mg/L (rat)		
. Drimany irritant offoct:				

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

(Contd. of page 7)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

· 12.1 Toxicity

Aquatic toxicity:		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
EC50	3 mg/L (daphnia magna)	
CAS: 78-93-3 butanone		
LC0/96 h	2,993 mg/L (pimephales promelas)	
EC50/48 h	308 mg/L (daphnia magna)	
Hydrocarbons, C9-12, n-alkanes, isoalkanes, cyclics, (2-25%) aromatics		
EC50/48 h 10-22 mg/L (daphnia magna)		

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

	(Contd. of page 8)	
· European waste catalogue		
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP14	Ecotoxic	

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1133

· 14.2 UN proper shipping name

· ADR 1133 ADHESIVES, ENVIRONMENTALLY

HAZARDOUS

1133 ADHESIVES, ENVIRONMENTALLY

**HAZARDOUS** 

· **IMDG** ADHESIVES, MARINE POLLUTANT

· IATA ADHESIVES

· 14.3 Transport hazard class(es)

· ADR





· Class 3 (F1) Flammable liquids.

· Label

· IMDG





· Class 3 Flammable liquids.

· Label 3

(Contd. on page 10)



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

(Contd. of page 9)

· IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group

· ADR, IMDG, IATA

• 14.5 Environmental hazards: Product contains environmentally hazardous

substances: Hydrocarbons, C7, n-alkanes, isoalkanes,

cyclics

Marine pollutant: Yes

Symbol (fish and tree)

· Special marking (ADR): Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): -

· **EMS Number:** F-E,S-D

· Stowage Category A

• 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

Tunnel restriction code E

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1133 ADHESIVES, 3, III, ENVIRONMENTALLY

3

**HAZARDOUS** 

- GB



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

(Contd. of page 10)

## **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) "GB- CLP" UK SI 2019 No. 720 The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019

"UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

CAS: 78-93-3 butanone

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

CAS: 78-93-3 butanone

3

- · National regulations:
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · Other regulations, limitations and prohibitive regulations No further relevant information available.
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 12)



Printing date 02.11.2022 Version number 8 Revision: 02.11.2022

Trade name: illbruck ME901

(Contd. of page 11)

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

## Department issuing SDS:

Prepared and verified in accordance with Annex II, Part A, 0.2.3. of "UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* Data compared to the previous version altered.

GB -