

NUDURA 6" (152mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

FORM PANELS c/w
INSERT WEBS-CUT
TO SUIT FLOOR
CONNECTION-ADDITIONAL
FORM SUPPORT AS
REQUIRED

WET SET FIELD
DOWELS FIELD BENT
INTO SLAB AS
SPECIFIED

THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

NUDURA 6"
(152mm) BRICK
LEDGE FORM UNIT

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

NUDURA WATERPROOF
MEMBRANE

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

STEEL DECK SUPPORT
WELDING ANCHOR
INSERT

COMPOSITE STEEL
DECK-SLAB AND
REINFORCEMENT AS
SPECIFIED

INTERIOR INSULATION
TO BE DISCONTINUOUS
AT FLOOR LINES

OWSJ

MINIMUM $\frac{1}{32}$ " (0.8mm) x 2
 $\frac{1}{2}$ " (63.5mm) GALVANIZED
STEEL CHANNEL CAP TO
PROVIDE THERMAL BARRIER
PROTECTION

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR
AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
COMPOSITE STEEL DECK-SLAB
STEEL JOISTS ON SIDE WALL
BRICK VENEER FINISH

REV. NO.
006 KS

REV. DATE:
MARCH 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.

D6C06

SCALE:
1 : 8