



1213



2538

Tremco CPG Netherlands B.V

Vlietskade 1032

NL-4241 Arkel

14

22

FA880-20140628

illbruck.com/dop/FA880

**EN 15651-1, -3, -4: 2012**

Non-structural sealant for joints for interior and exterior application  
(intended for use in cold climates)

Non-structural sealant for sanitary joints

Sealant for movement joints in floors for interior and exterior application  
(intended for use in cold climates)

- Type F-EXT-INT-CC 20HM, Type S XS 1, Type PW-EXT-INT-CC 12.5E

- Conditioning: Method A

- Substrate: Mortar M1 with Primer AT101, Aluminium with Primer AT140,  
Glass

**REACTION TO FIRE (EN 13501)**

Class E

**RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH**

NPD

**WATER TIGHTNESS AND AIR TIGHTNESS**

- Resistance to flow	≤ 3mm
----------------------	-------

- Loss of volume	≤ 10%
------------------	-------

- tear resistance	NF
-------------------	----

- adhesion/cohesion properties at maintained extension after water immersion (28 days/23°C)	NF
---	----

- adhesion/cohesion properties at maintained extension after salt water immersion (28 days/23°C)	NF
--	----

- tensile properties at maintained extension (-30°C)	NF
--	----

- tensile properties, maintained extension after water immersion at 23°C	Pass
--	------

**MICROBIOLOGICAL GROWTH**

0

**DURABILITY**

Pass

NF = no failure according to ISO 11600

NPD = No performance declared