

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758



Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Nullifire SC604

· MSDS code: W-N-SC604

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Coating compound/ Surface coating/ paint

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Tremco CPG UK Ltd
Coupland Road, Hindley Green, WIGAN, WN2 4HT
Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410
msds@cpg-europe.com

· Further information obtainable from:

Tremco CPG UK Ltd
Coupland Road, Hindley Green, Wigan, WN2 4HT
T: +44 (0) 1942251400, F: +44 (0) 1942251410
www.cpg-europe.com, info.uk@cpg-europe.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Carc. 2 H351 Suspected of causing cancer.
Repr. 2 H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

—GB—

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Warning· **Contains:**

toluene
melamine
butanone

· **Hazard statements**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H351 Suspected of causing cancer.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P284 Wear respiratory protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.

· **Supplemental information:**

Restricted to professional users.

· **Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC**

VOC 2004/42/CE & UK SI 2012/1715 (A / i) = <500 g/l
Nullifire SC604
= 317 g/l

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Determination of endocrine-disrupting properties**

CAS: 78-93-3 butanone

List II

— GB —

(Contd. on page 3)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758



Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:

CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-xxxx	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	10-<20%
CAS: 108-78-1 EINECS: 203-615-4 Reg.nr.: 01-2119485947-16-xxxx	melamine Carc. 2, H351; Repr. 2, H361f; STOT RE 2, H373	5-<10%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	1-<5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	1-<5%

• **EU SVHC** see Section 15

• **GB SVHC** see Section 15

Additional information:

For the wording of the listed hazard phrases refer to section 16.

Fillers are encapsulated within the liquid and therefore not expected to be released from the product under normal conditions of use.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:** Do not induce vomiting; call for medical help immediately.

• **Information for doctor:** No further relevant information available.

(Contd. on page 4)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758



Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 3)

· **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Nausea

May cause damage to organs through prolonged or repeated exposure.

Irritating to eyes, respiratory system and skin.

Harmful: may cause lung damage if swallowed.

May damage fertility or the unborn child.

Suspected of causing cancer.

· **Hazards** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758



Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 4)

Avoid breathing vapours/spray.

Pregnant women should strictly avoid inhalation or skin contact.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Information about fire - and explosion protection:

Flammable.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

Provide ventilation for receptacles.

Information about storage in one common storage facility: Protect from heat and direct sunlight.**Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Storage temperature: 0°C to +35°C

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 108-88-3 toluene**

WEL	Short-term value: 384 mg/m ³ , 100 ppm
	Long-term value: 191 mg/m ³ , 50 ppm
Sk	

CAS: 78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm
	Long-term value: 600 mg/m ³ , 200 ppm
Sk, BMGV	

CAS: 1330-20-7 xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m ³ , 50 ppm
Sk; BMGV	

DNELs**CAS: 108-78-1 melamine**

Inhalative	DNEL	8.3 mg/m ³ (workers) (systemic effects)
------------	------	--

PNECs**CAS: 78-93-3 butanone**

PNEC	55.8 mg/L (fresh water)
	709 mg/L (sewage treatment plant)

(Contd. on page 6)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 5)

PNEC	55.8 mg/L (sporadic release)
	55.8 mg/L (salt water)
	22.5 mg/kg (soil)
	284.7 mg/kg (sediment (salt water))
	284.7 mg/kg (sediment (fresh water))

Ingredients with biological limit values:**CAS: 78-93-3 butanone**

BMGV	70 µmol/L
	Medium: urine
	Sampling time: post shift
	Parameter: butan-2-one

CAS: 1330-20-7 xylene (mix)

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

Additional information:

The lists valid during the making were used as basis.

Fillers are encapsulated within the liquid and therefore not expected to be released from the product under normal conditions of use.

8.2 Exposure controls**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Ensure good ventilation/exhaustion at the workplace.

Do not breathe spray.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Wear respiratory protection.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Filter A/P2

For further guidance,
please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

Hand protection

Protective gloves

(Contd. on page 7)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 6)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

PVA gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye/face protection**



Tightly sealed goggles

- **Body protection:**



Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

· Colour:	White
· Odour:	Solvent-like
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	110 °C
· Lower and upper explosion limit	
· Lower:	0.7 Vol %
· Upper:	7.0 Vol % (CAS: 108-88-3 toluene)
· Flash point:	26 °C
· Ignition temperature:	500 °C
· Viscosity:	
· Kinematic viscosity at 40 °C	>20.5 mm ² /s

(Contd. on page 8)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758



Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 7)

<ul style="list-style-type: none"> · Solubility · water: · Vapour pressure at 20 °C: · Density and/or relative density · Density at 20 °C: 		<p>Immiscible / difficult to mix.</p> <p>29 hPa (CAS: 108-88-3 toluene)</p> <p>1.36 g/cm³</p>
<ul style="list-style-type: none"> · 9.2 Other information · Appearance: · Form: · Important information on protection of health and environment, and on safety. · Explosive properties: · Solvent content: · VOC (EU) · VOC (EC) · Solids content: 		<p>Liquid</p> <p>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</p> <p>317.0 g/l</p> <p>23.90 %</p> <p>69-75 % (v/v)</p>
<ul style="list-style-type: none"> · Information with regard to physical hazard classes · Explosives · Flammable gases · Aerosols · Oxidising gases · Gases under pressure · Flammable liquids · Flammable solids · Self-reactive substances and mixtures · Pyrophoric liquids · Pyrophoric solids · Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water · Oxidising liquids · Oxidising solids · Organic peroxides · Corrosive to metals · Desensitised explosives 		<p>Flammable liquid and vapour.</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p> <p>Void</p>

SECTION 10: Stability and reactivity

- **10.1 Reactivity Stable**

(Contd. on page 9)

GB

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758



Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 8)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Nitrogen oxides
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

CAS: 108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/L (mouse)

CAS: 108-78-1 melamine

Oral	LD50	3,161 mg/kg (rat)
------	------	-------------------

CAS: 78-93-3 butanone

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	34 mg/L (rat)

CAS: 1330-20-7 xylene (mix)

Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	27.124 mg/L (rat)
	LC50/4 h	5,000 ppmV (rat)

- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Irritating to eyes.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Suspected of causing cancer.
- **Reproductive toxicity**
Suspected of damaging fertility. Suspected of damaging the unborn child.
- **STOT-single exposure**
May cause drowsiness or dizziness.

(Contd. on page 10)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758



Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 9)

- **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

- **Aspiration hazard** Based on available data, the classification criteria are not met.

- **Additional toxicological information:**

Repeated exposure may cause skin dryness or cracking.

Harmful: may cause lung damage if swallowed.

Fillers are encapsulated within the liquid and therefore not expected to be released from the product under normal conditions of use.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

CAS: 78-93-3	butanone	List II
--------------	----------	---------

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 78-93-3 butanone	
LC0/96 h	2,993 mg/L (pimephales promelas)
EC50/48 h	308 mg/L (daphnia magna)
CAS: 1330-20-7 xylene (mix)	
LC50/96 h	4.2 mg/L (rainbow trout)
EC50/48 h	2.93-4.4 mg/L (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

- **12.7 Other adverse effects**

- **Ecotoxicological effects:**

CAS: 1330-20-7 xylene (mix)	
IC50/72 h	2.2 mg/L (algae)

- **Additional ecological information:**

- **General notes:**

The product contains materials that are harmful to the environment.

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

GB

(Contd. on page 11)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 10)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP10	Toxic for reproduction

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.
Non contaminated packagings may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1139

14.2 UN proper shipping name

ADR 1139 COATING SOLUTION
1139 COATING SOLUTION
IMDG, IATA COATING SOLUTION

14.3 Transport hazard class(es)

ADR



Class 3 (F1) Flammable liquids.
Label 3

(Contd. on page 12)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 11)

· **IMDG, IATA**

· **Class** 3 Flammable liquids.
 · **Label** 3

· **14.4 Packing group**
 · **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**
 · **Marine pollutant:** No

· **14.6 Special precautions for user** Warning: Flammable liquids.
 · **Hazard identification number (Kemler code):** 30
 · **EMS Number:** F-E, S-E
 · **Stowage Category** A

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· **ADR**
 · **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml
 · **Transport category** 3
 · **Tunnel restriction code** D/E

· **IMDG**
 · **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1139 COATING SOLUTION, 3, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 HSE EH40/2005 Workplace Exposure Limits (as amended)
 Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)
 STATUTORY INSTRUMENTS 2012 No. 1715 ENVIRONMENTAL PROTECTION | The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012, and any subsequent amendments

(Contd. on page 13)

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758



Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 12)

"GB- CLP" UK SI 2019 No. 720 The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019

"UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

The Endocrine Disruptor Lists I, II, III (www.edlists.org)

- **Directive 2012/18/EU**

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 48

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

CAS: 108-88-3	toluene	3
CAS: 78-93-3	butanone	3

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

CAS: 108-88-3	toluene	3
CAS: 78-93-3	butanone	3

- **National regulations:**

- **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- **Other regulations, limitations and prohibitive regulations** No further relevant information available.

- **Substances of very high concern (SVHC) according to EU REACH, Article 57**

CAS: 108-78-1	melamine
---------------	----------

- **Substances of very high concern (SVHC) according to UK REACH** Not applicable.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

(Contd. on page 14)

GB

Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758



Printing date 26.04.2023

Version number 3 (replaces version 2)

Revision: 26.04.2023

Trade name: Nullifire SC604

(Contd. of page 13)

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

• **Department issuing SDS:**

Prepared and verified in accordance with Annex II, Part A, 0.2.3. of "UK- REACH" UK SI 2019 No. 758
The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

• **Date of previous version:** 03.08.2021

• **Version number of previous version:** 2

• **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

• *** Data compared to the previous version altered.**