

Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: TREMCO CS900 A
- · MSDS code: W-T-CS900A
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Epoxy resin
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Tremco CPG UK Ltd

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@cpg-europe.com

· Further information obtainable from:

Tremco CPG UK Ltd

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.cpg-europe.com, info.uk@cpg-europe.com

1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS09

(Contd. on page 2)



Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900 A

(Contd. of page 1)

- · Signal word Warning
- · Contains:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P264 Wash thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

· Supplemental information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

 Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC

VOC 2004/42/CE (A / j) = <500 g/l

TREMCO CS900 A

- = (ready to use, mixed product) <500 g/l
- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number $50-4$ NLP: 500-033-5 average molecular weight ≤ 700)		50-<75%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 100-51-6	Benzyl alcohol	5-<10%
EINECS: 202-859-9	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	

- · SVHC -
- · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

- GB



Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900 A

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · **General information:** Take affected persons out of danger area and lay down.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

Immediately remove all soiled and contaminated clothing

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Seek immediate medical advice.

- · Information for doctor: No further relevant information available.
- · 4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Irritating to eyes and skin.

Coughing

- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Carbon dioxide (CO2)

- 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Ensure adequate ventilation.

Keep people at a distance and stay on the windward side.

(Contd. on page 4)



Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900 A

(Contd. of page 3)

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

When the product is mixed, it is recommended to be used in less than 20 minutes.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Contains epoxy constituents. See information supplied by the manufacturer.

- Information about fire and explosion protection: The product is not flammable.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility:

Protect from heat and direct sunlight.

Store away from foodstuffs.

Store away from reducing agents.

· Further information about storage conditions:

Store receptacle in a well ventilated area.

Storage temperature: +5°C to +25°C

Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 5)



Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900 A

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Recommendation:

Use only in well-ventilated areas.

Fresh air mask

Use suitable respiratory protective device in case of insufficient ventilation.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

· Protection of hands:



Protective gloves

· Material of gloves

Nitrile rubber, NBR

PVA gloves

Neoprene gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- Appearance:

Form: Liquid

Colour: According to product specification

(Contd. on page 6)



Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900 A

		(C	contd. of page 5)
· Odour:	Characteristic		
· pH-value: · Melting point/freezing point:	Not determined. Undetermined.		
· Flash point:	>100 °C		
· Explosive properties:	Product does not present an explosion hazard.		
Density:	Not determined.		
 Solubility in / Miscibility with water: 	Insoluble.		
· Solvent content: VOC (EU)	<500 g/l (mixed product)		
· 9.2 Other information	No further relevant information available.		

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Forms heat.

Exothermic reaction.

Reacts with acids, alkalis and oxidising agents.

- · 10.4 Conditions to avoid Keep away from heat.
- 10.5 Incompatible materials: Reacts with acids, alkalis and oxidising agents.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

CAS: 100-51-6 Benzyl alcohol				
Oral	LD50	1,230 mg/kg (rat)		
	LD50	2,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>4,178 mg/L (rat)		

- Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

(Contd. on page 7)



Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900 A

(Contd. of page 6)

- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- · Additional toxicological information: Irritating to respiratory system.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: Toxic to aquatic life with long lasting effects.
- · 12.2 Persistence and degradability Not easily biodegradable
- · 12.3 Bioaccumulative potential May be accumulated in organism
- · 12.4 Mobility in soil Mobile.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- · Recommendation

Disposal must be made according to official regulations.

Cured product can be deposited together with domestic waste. Observe the specific related regulations of local authorities.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
08 01 11*	08 01 11* waste paint and varnish containing organic solvents or other hazardous substances	
HP4	Irritant - skin irritation and eye damage	
HP13	Sensitising	
HP14	Ecotoxic	

(Contd. on page 8)



Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900 A

(Contd. of page 7)

- Uncleaned packaging:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Non contaminated packagings may be recycled.

SECTION 14: Transport information
· 14.1 UN-Number
· ADR, IMDG, IATA

14.2 UN proper shipping name

· ADR 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A epoxy resin (number average MW ≤700), Solvent naphtha

UN3082

(petroleum), light arom.)

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A epoxy resin (number average MW ≤700), Solvent naphtha

(petroleum), light arom.)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, · IMDG LIQUID, N.O.S. (bisphenol A epoxy resin (number

average MW ≤700), Solvent naphtha (petroleum), light

arom.), MARINE POLLUTANT

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, · IATA LIQUID, N.O.S. (bisphenol A epoxy resin (number

average MW ≤700), Solvent naphtha (petroleum), light arom.)


- · 14.3 Transport hazard class(es)
- · ADR



· Class 9 (M6) Miscellaneous dangerous substances and articles.

· Label

· IMDG, IATA



Class 9 Miscellaneous dangerous substances and articles.

(Contd. on page 9)



Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900

	(Contd. of page
Label	9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances: bisphenol A epoxy resin (number average MW ≤700)
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances a
Hazard identification number (Kemler code):	90
EMS Number: Stowage Category	F-A,S-F A
Marpol and the IBC Code Transport/Additional information:	Not applicable.
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (BISPHENOL EPOXY RESIN (NUMBER AVERAGE MW ≤700 SOLVENT NAPHTHA (PETROLEUM), LIGH AROM.), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

(Contd. on page 10)



Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900 A

(Contd. of page 9)

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC

2001/118/EC as regards the list of wastes

2008/98/EC on waste

- · Directive 2012/18/EU
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · National regulations:
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 11)



(Contd. of page 10)

Printing date 01.02.2021 Version number 5 Revision: 01.02.2021

Trade name: TREMCO CS900 A

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - oral – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.