

DoP No. **FS703-20220107**

Version No. **06**

- According to Annex III of regulation (EU) No. 305/2011, Amended by commission delegated regulation (EU) No.574/2014



CE Certificate No.: 2812-CPR-JA5052



Nullifire FS703 Fire Resistant Silicone sealant

Intended use/es : Nullifire FS703 is to reinstate the fire resistance performance of gaps in and joints between rigid wall constructions, gaps in and joints between rigid floor constructions.

- Manufacturer(s):**
- Tremco CPG UK Limited**
Coupland Road, Hindley Green
Wigan - WN2 4HT (United Kingdom)
- Authorised representative :**
- Tremco CPG Netherlands B.V.**
Vlietskade 1032
4241 WC Arkel (Netherlands)

European Assessment Method

European Assessment Document	EAD 350454-00-1104 (Sept. 2017)
European Technical Assessment	ETA 20/1215
Technical Assessment Body	Element Materials Technology Rotterdam B.V.
Notified body/ies	Element Materials Technology Rotterdam B.V NB : 2812

System/s of AVCP

1

Declared performance/s

Linear joint and Gap Seals_ (EAD 350141-00-1106 (Sept. 2017))			
No.	Essential Characteristic	Standards	Performance
BWR2	Safety in case of fire		
1	Reaction to fire	EN 13501-1	Class F
2	Fire Resistance	EN 13501-2	Class Up to EI 240

Linear joint and Gap Seals_ (EAD 350141-00-1106 (Sept. 2017))

No.	Essential Characteristic	Standards	Performance
BWR3	Hygiene, Health and the Environment		
3	Content, emission and/ or release of dangerous substances	EOTA TR034	IA1 & S/W2
4	Air permeability (material property)	EN 1026	Air tight up to 600 [Pa]
5	Water permeability (material property)	Annex C	NPD
BWR4	Safety and accessibility		
6	Mechanical resistance and stability	EOTA TR001	< not applicable >
7	Resistance to impact / movement	EOTA TR001	< not applicable >
8	Adhesion	EOTA TR001	Adhesive with Mc < 7,5 [%]
9	Durability	§ 2.2.12	Type X
10	Movement capability	Annex B.13	Less than < 7,5 %
11	Cycling of perimeter seals for curtains walls	§ 2.2.14	< not applicable >
12	Compression set	Annex B.14	< not applicable >
13	Linear expansion on setting	Annex B.11.2	< not applicable >
BWR5	Protection against noise		
14	Airborne sound insulation	ISO 10140	NPD
BWR6	Energy economy and heat retention		
15	Thermal properties	§ 2.2.10	NPD
16	Water vapor permeability	§ 2.2.11	NPD

*NPD: No Performance Declared

Appropriate Technical Documentation and/or Specific Technical Documentation:


Annex:

- According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according to Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance


Declaration of Performance (DoP)

No. FS703-20220107 | Version No. 06

Label "Long Sign"

 15	
CE / NB 2812 Certificate No. 2812-CPR-JA5052	
Tremco CPG UK Ltd Hindley Green, Wigan, WN2 4HT, UK	
DOP No. FS703-20220107	
Nullifire FS703 Silicone Sealant used for linear seal www.nullifire/FS703	
Declared Performance/s	
Fire Resistance	Class 30 Up to 240 [min] (See ETA's Annex C)
Air permeability	Air tight up to 600 [Pa]
Durability	Type X
Movement capability	Less than 7.5%
ETA 20/1215 EAD 350141-00-1106 (Sept. 2017)	

Label "Short Sign"

www.nullifire/FS703	 15
	CE / NB 2812
	Tremco CPG UK Ltd Hindley Green, Wigan, WN2 4HT, UK
	DOP No. FS703-20220107
	ETA 20/1215 EAD 350141-00-1106 (Sept. 2017) Linear joint and gap seals

Disclaimer

- The performance of the product identified above is in conformity with the set of declared performance/s.
- This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot , Operations Director

At Wigan on 03/03/2026

-- END OF DOCUMENT --