Page 1/13



Safety data sheet acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Finding date 04.09.202	
SECTION 1: Io undertaking	dentification of the substance/mixture and of the company/
• 1.1 Product identif	ier
[.] Trade name: <u>illbru</u>	ck FM110
No further relevant i	/110 fied uses of the substance or mixture and uses advised against information available. substance / the mixture Sealant
 Manufacturer/Supp Tremco CPG Nethe Vlietskade 1032, 42 	rlands B.V. 41 WC Arkel 00, F: +31 (0) 183568100
T: +44 (0) 19422514	
	ephone number: s tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 otland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a
SECTION 2: Haz	zards identification
 Classification according 	
Eye Irrit. 2 H31	9 Causes serious eye irritation.
Resp. Sens. 1 H33	
Skin Sens. 1 H31	,
Carc. 2 H35	
STOT SE 3 H33	
STOT RE 2 H37	3 May cause damage to organs through prolonged or repeated exposure.
-	g to Regulation (EC) No 1272/2008 sified and labelled according to the CLP regulation. (Contd. on page 2) GB



Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

Hazard pictogram		(Contd. of page 1
Hazard pictogran	^	
	V	
GHS02 GHS07	HS08	
Signal word Dang	er	
Contains:		
diphenylmethaned	socyanate, isomers and homolog	ues
Hazard statemen	; ;	
H222-H229 Extrer	ely flammable aerosol. Pressurise	ed container: May burst if heated.
H332 Harmf	l if inhaled.	
H315 Cause	skin irritation.	
	s serious eye irritation.	
		or breathing difficulties if inhaled.
	use an allergic skin reaction.	
	ted of causing cancer.	
	use respiratory irritation.	
5	use damage to organs through p	olonged or repeated exposure.
Precautionary sta		
		parks, open flames and other ignition sources. N
smok		
P211 Do not spray on an open flame or other ignition source.		
	pierce or burn, even after use.	
	breathe dust/fume/gas/mist/vapo	
	of inadequate ventilation wear re	
	riencing respiratory symptoms: C	
	•	temperatures exceeding 50 °C/122 °F.
Supplemental inf		rain reaction
	socyanates. May produce an aller	d before industrial or professional use.
2.3 Other hazards		u belore industrial or professional use.
	d vPvB assessment	
PBT: Not applicab		
vPvB: Not applicat		
SECTION 3. C	mposition/information on i	naredients
		ngreatents
3.2 Mixtures		
-	e substance with propellant	
Dangerous comp	nents:	
CAS: 9016-87-9		iisocyanate, isomers and homologues 30-<50%
EC number: 618-4	8-9 Resp. Sens. 1, H3	34; Carc. 2, H351; STOT RE 2, H373;
		32; Skin Irrit. 2, H315; Eye Irrit. 2, H319;
	Skin Sens. 1, H31	7; STOT SE 3, H335
		(Contd. on page 3



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

	(Con	td. of page 2)
CAS: 1244733-77-4	tris(2-chloro-1-methylethyl)phosphate	10-<20%
EC number: 807-935-0	Acute Tox. 4, H302	
Reg.nr.: 01-2119486772-26-xxxx		
CAS: 115-10-6	dimethyl ether	5-<10%
EINECS: 204-065-8	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119472128-37-xxxx		
CAS: 75-28-5	isobutane	5-<10%
EINECS: 200-857-2	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27-xxxx		
EC number: 926-564-6	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol,	1-<5%
Reg.nr.: 01-2119971810-36-xxxx	propoxylated	
	Acute Tox. 4, H302	
CAS: 74-98-6	propane	1-<5%
EINECS: 200-827-9	Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
Reg.nr.: 01-2119486944-21-xxxx		

· SVHC -

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

While curing the following substances are formed and released by a reaction with atmospheric humidity: Carbon dioxide (CO2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out of danger area and lay down.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove all soiled and contaminated clothing If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- · Information for doctor: No further relevant information available.
- 4.2 Most important symptoms and effects, both acute and delayed May cause an allergic skin reaction.
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 Irritating to eyes, respiratory system and skin.
 Harmful if inhaled.

Suspected of causing cancer.



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110 (Contd. of page 3) May cause damage to organs through prolonged or repeated exposure. · Hazards No further relevant information available. • 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available. **SECTION 5: Firefighting measures** 5.1 Extinguishing media Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · For safety reasons unsuitable extinguishing agents: Water with full jet · 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. Carbon monoxide (CO) Carbon dioxide (CO2) Nitrogen oxides (NOx) Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.: Hydrogen cyanide (HCN) 5.3 Advice for firefighters • **Protective equipment:** Wear self-contained respiratory protective device. SECTION 6: Accidental release measures • 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Avoid contact with the eyes and skin. Ensure adequate ventilation. 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. · 6.3 Methods and material for containment and cleaning up: Dispose of contaminated material as waste according to Section 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. **SECTION 7: Handling and storage** · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Avoid contact with the eyes and skin. Avoid breathing vapours/spray. Wear suitable protective clothing and gloves. The usual precautionary measures are to be adhered to when handling chemicals.

(Contd. on page 5)



Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

(Contd. of page 4)

	ation about fire - and explosion protection:
	nely flammable aerosol.
	irised container: May burst if heated. spray onto a naked flame or any incandescent material.
	t against electrostatic charges.
	irised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i
	c lights. Do not pierce or burn, even after use.
	away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
· 7 2 Co	nditions for safe storage, including any incompatibilities
Storag	
0	rements to be met by storerooms and receptacles:
	e official regulations on storing packagings with pressurised containers.
	ation about storage in one common storage facility: Store away from water.
	r information about storage conditions:
	n cool, dry conditions in well sealed receptacles.
	seal receptacle gas tight. t from heat and direct sunlight.
	ecific end use(s) No further relevant information available.
<u> </u>	
• 8.1 Co	ION 8: Exposure controls/personal protection ntrol parameters
· 8.1 Col · Additic	ntrol parameters onal information about design of technical facilities: No further data; see item 7.
· 8.1 Cor · Additic · Ingred	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace:
· 8.1 Col · Additic · Ingred CAS: 9	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues
• 8.1 Con • Additio • Ingred CAS: 9 WEL	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³
· 8.1 Con · Additio · Ingred CAS: 9 WEL	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³
• 8.1 Col • Additio • Ingred CAS: 9 WEL	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO
• 8.1 Co • Additio • Ingred CAS: 9 WEL S L S CAS: 1	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO
• 8.1 Col • Additic • Ingred CAS: 9 WEL S CAS: 1 WEL S	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO I15-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm
• 8.1 Col • Additic • Ingred CAS: 9 WEL CAS: 1 S CAS: 1 WEL L	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO I15-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm
· 8.1 Co · Additio · Ingred CAS: 9 WEL 5 L CAS: 1 WEL 5 L · PNECS	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO I15-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm
• 8.1 Co • Additic • Ingred CAS: 9 WEL CAS: 1 WEL CAS: 1 • PNECs CAS: 9	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm
• 8.1 Co • Additic • Ingred CAS: 9 WEL CAS: 1 WEL CAS: 1 • PNECs CAS: 9	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm s 0016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water)
• 8.1 Co • Additic • Ingred CAS: 9 WEL CAS: 1 WEL CAS: 1 • PNECs CAS: 9	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm Source-term value: 766 mg/m ³ , 400 ppm So
· 8.1 Co · Additic · Ingred CAS: 9 WEL 5 L CAS: 1 WEL 5 L · PNECs CAS: 9 PNEC	ntrol parameters onal information about design of technical facilities: No further data; see item 7. iients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO I15-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm s 0016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water)
• 8.1 Co • Additic • Ingred CAS: 9 WEL CAS: 1 WEL CAS: 1 • PNEC CAS: 9 PNEC	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm S 0016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water) 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate
• 8.1 Co • Additic • Ingred CAS: 9 WEL CAS: 1 WEL CAS: 1 • PNEC CAS: 9 PNEC	ntrol parameters onal information about design of technical facilities: No further data; see item 7. ients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm So 016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water) 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate 0.64 mg/L (fresh water)
• 8.1 Col • Additic CAS: 9 WEL 5 L CAS: 1 WEL 5 L S CAS: 1 VWEL 5 L S CAS: 1 PNEC CAS: 1 PNEC	ntrol parameters onal information about design of technical facilities: No further data; see item 7. iients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm _ong-term value: 766 mg/m ³ , 400 ppm _ong-term value: 766 mg/m ³ , 400 ppm
• 8.1 Col • Additic CAS: 9 WEL 5 L CAS: 1 WEL 5 L S CAS: 1 VWEL 5 L S CAS: 1 PNEC CAS: 1 PNEC	ntrol parameters onal information about design of technical facilities: No further data; see item 7. iients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm 5 016-87-9 diphenylmethanediisocyanate, isomers and homologues 1 mg/L (fresh water) 10 mg/L (intermittent release) 0.1 mg/L (salt water) 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate 0.64 mg/L (fresh water) 0.064 mg/L (marine) 1.7 mg/kg dwt (soil)
• 8.1 Col • Additic CAS: 9 WEL 5 L CAS: 1 WEL 5 L S CAS: 1 VWEL 5 L S CAS: 1 PNEC CAS: 1 PNEC	ntrol parameters onal information about design of technical facilities: No further data; see item 7. iients with limit values that require monitoring at the workplace: 0016-87-9 diphenylmethanediisocyanate, isomers and homologues Short-term value: 0.07 mg/m ³ _ong-term value: 0.02 mg/m ³ Sen; as -NCO 115-10-6 dimethyl ether Short-term value: 958 mg/m ³ , 500 ppm _ong-term value: 766 mg/m ³ , 400 ppm _ong-term value: 766 mg/m ³ , 400 ppm _ong-term value: 766 mg/m ³ , 400 ppm



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

(Contd. of page 5) CAS: 115-10-6 dimethyl ether PNEC 0.155 mg/L (fresh water) 160 mg/L (sewage treatment plant) 1.549 mg/L (intermittent release) 0.016 mg/L (salt water) PNEC 0.045 mg/kg (soil) 0.069 mg/kg (sediment (salt water)) 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol, propoxylated PNEC 10 mg/L (sewage treatment plant) · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls Personal protective equipment: · General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Ensure that washing facilities are available at the work place. Avoid contact with the eyes and skin. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear suitable protective clothing and gloves. **Respiratory protection:** In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. For further guidance. please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide". Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves Nitrile rubber. NBR Recommended thickness of the material: ≥ 0.4 mm Butyl rubber, BR Recommended thickness of the material: ≥ 0.7 mm



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

(Contd. of page 6)

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

· Eye protection:

Tightly sealed goggles

Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

 9.1 Information on basic physical General Information 	and chemical properties
· Appearance:	
Form:	Aerosol
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Mixture reacts violently with water.
 Melting point/freezing point: 	Not applicable, as aerosol.
	Undetermined.
· Flash point:	-97 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	460 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	18.6 Vol %
· Vapour pressure at 20 °C:	0 hPa
· Density at 20 °C:	1.04 g/cm ³
· Relative density	Not determined.
	(Contd. on page



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

		(Contd. of page 7)
· Vapour density	Not determined.	
Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Immiscible / difficult to mix.	
· Partition coefficient: n-octanol	water: Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC (EU)	181.2 g/l	
VOC (EC)	17.42 %	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (prussic acid)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Harmful if inhaled.

 LD/LC50 values relevant for classification: 			
CAS: 9	016-87-9 di	phenylmethanediisocyanate, isomers and homologues	
Oral		>10,000 mg/kg (rat)	

Ulai	LDSU	~10,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

Inhalative LC50/4 h 1.5 mg/L (rat)

(Contd. on page 9)

GB -



Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

rade name:	illbruck F	M110		
			(Contd. of page 8)	
CAS: 124	4733-77-4	l tris(2-chloro-1-methylethyl)phosphate		
Oral	LD50	632 mg/kg (rat)		
CAS: 115	5-10-6 dim	ethyl ether		
Inhalative	e LC50/4 ł	n 308 mg/L (rat)		
2,2',6,6'-1	etrabrom	o-4,4'-isopropylidenediphenol, propoxylated		
Oral	LD50	732 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)		
· Primary			,	
	rosion/irri			
-	kin irritatio			
	erious eye	ge/irritation		
		n sensitisation		
		or asthma symptoms or breathing difficulties if inhaled.		
		gic skin reaction.		
		ogical information:		
	CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)			
	 Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Suspected of causing cancer. 			
• Reproductive toxicity Based on available data, the classification criteria are not met. • STOT-single exposure				
		bry irritation.		
· STOT-re		to organs through prolonged or repeated exposure.		
•	•	Based on available data, the classification criteria are not met.		
-				
		cological information		
· 12.1 Tox	-			
•	-	ohenylmethanediisocyanate, isomers and homologues		
LC0/96 h	-	mg/L (brachydanio rerio)		
		mg/L (daphnia magna)		
		l tris(2-chloro-1-methylethyl)phosphate		
		(pimephales promelas)		
		nd degradability No further relevant information available. The product is not easily biodegradable.		
		ive potential No further relevant information available.		
		il No further relevant information available		

12.4 Mobility in soil No further relevant information available.



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

(Contd. of page 9)

Ecotoxical effects:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

NOEC/21 d >10 mg/L (daphnia magna)

· Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

Do not pierce or burn, even after use.

· European	waste catalogue
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
08 05 01*	waste isocyanates
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising

· Uncleaned packaging:

• **Recommendation:** Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport information · 14.1 UN-Number · ADR, IMDG, IATA UN1950 · 14.2 UN proper shipping name · ADR 1950 AEROSOLS · 1950 AEROSOLS · IMDG AEROSOLS · IATA AEROSOLS, flammable



rinting date 04.09.2021 Vers	sion number 11	Revision: 04.09.20
ade name: illbruck FM110		
		(Contd. of page
· 14.3 Transport hazard class(es)		
ADR		
· Class	2 5F Gases.	
· Label	2.1	
· IMDG, IATA		
Class	2.1	
· Label	2.1	
 14.4 Packing group ADR, IMDG, IATA 	Void	
 14.5 Environmental hazards: Marine pollutant: 	No	
14.6 Special precautions for user	Warning: Gases.	
 Hazard identification number (Kemler code EMS Number: 	e): - F-D,S-U	
· Stowage Code	SW1 Protected from sourc	es of heat
	SW22 For AEROSOLS wir litre: Category A. For AE above 1 litre: Category B. Category C, Clear of living	th a maximum capacity o EROSOLS with a capac . For WASTE AEROSOL
· Segregation Code	SG69 For AEROSOLS wit litre: Segregation as for class	th a maximum capacity o
	class 1 except for division	•
	For AEROSOLS with a cap	pacity above 1 litre:
	Segregation as for the app 2.	propriate subdivision of cla
	Z. For WASTE AEROSOLS:	
	Segregation as for the app 2.	propriate subdivision of cla
 14.7 Transport in bulk according to Annex Marpol and the IBC Code 		
	Not applicable.	(Contd. on page



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

		(Contd. of page 11)
· Transport/Additional information:		
· ADR		
 Limited quantities (LQ) 	1L	
Excepted quantities (EQ)	Code: E0	
,	Not permitted as Excepted Quantity	
 Transport category 	2	
Tunnel restriction code	D	
· IMDG		
 Limited quantities (LQ) 	1L	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture "EU-CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1)
 "EU-REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments) COMMISSION REGULATION (EU) 2020/878 of 18 June 2020.
 75/324/EEC relating to aerosol dispensers HSE EH40/2005 Workplace Exposure Limits (as amended) Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)
 "GB-CLP" The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019
 "UK-REACH" The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020
 Directive 2012/18/EU
 Qualificing quantity (tennee) for the application of lower tier requirements 150 t
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $500\ t$
- National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed. Employment restrictions concerning pregnant and lactating women must be observed.

- · Other regulations, limitations and prohibitive regulations No further relevant information available.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

(Contd. on page 13)



acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 04.09.2021

Version number 11

Revision: 04.09.2021

Trade name: illbruck FM110

(Contd. of page 12) H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. Department issuing SDS: Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3. Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 * * Data compared to the previous version altered. GB