
Safety Data Sheet according to Regulation (EC) 'No. 2015/830















SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

FLOWCHEM VE RC-RESIN **Revision Date:** 01/09/2021 Product Identifier 1.1

Supersedes Date: 21/09/2018 Flowchem VE RC-Resin **Product Name:**

52C1-X0JJ-1005-X9S3 **UFI Code:**

Relevant identified uses of the substance or mixture and uses

advised against

For use by appropriately trained applicators. Advised against: Home DIY applications, because of the health hazards and training required. Component of multicomponent

coatings - Professional use only.

Details of the supplier of the safety data sheet 1.3

> Flowcrete UK Ltd. Supplier:

The Flooring Technology Centre

Booth Lane

Moston, Sandbach, Cheshire. UK

CW11 3QF

Tel: +44 (0)1270 753000 Fax: +44 (0)1270 753333 ehs.uk@flowcrete.com http://www.flowcrete.co.uk

ehs.uk@flowcrete.com **Datasheet Produced by:**

Emergency telephone number: CHEMTREC +001 703 5273887 (Outside US)

CHEMTREC 1-800-424-9300 (Inside US)

Giftinformasjonen: +47 22 59 13 00

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 3 Skin Irritation, category 2

H226 H315

Eye Irritation, category 2	H319
Acute Toxicity, Inhalation, category 4	H332
STOT, single exposure, category 3, RTI	H335
Reproductive_ToxicityD_category_2	H361d
STOT, repeated exposure, category 1	H372
Hazardous to the aquatic environment, Chronic, category 3	H412

2.2 Label elements

Symbol(s) of Product







Signal Word

Danger

Named Chemicals on Label

Styrene

HAZARD STATEMENTS

E	11000	Florenselde Berild and conserve
Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Reproductive_ToxicityD_category_2	H361d	Suspected of damaging the unborn child.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/
		face protection.
	P284	Wear respiratory protection.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P308+313	IF exposed or concerned: Get medical advice/attention.
	P314	Get medical advice/attention if you feel unwell.
	P332+313	If skin irritation occurs: Get medical advice/attention.
	P403+233	Store in a well-ventilated place. Keep container tightly

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

SECTION 3: Composition/Information On Ingredients

3.2 Mixtures

closed.

335-361d-372

Hazardous ingredients

Name According to EEC EINEC No. CAS-No. % Classifications

Styrene 202-851-5 100-42-5 50 - <75 H226-304-315-319-332- Acute Tox. 4 Inhalation,

Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Repr. 2, Skin Irrit. 2, STOT RE 1, STOT SE 3 RTI

<u>CAS-No.</u> <u>M-Factors</u> <u>REACH Reg No.</u>

100-42-5 01-2119457861-32

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance. Remove contaminated clothing and shoes.

AFTER INHALATION: Move to fresh air. Remove person to fresh air. If signs/symptoms continue, get medical attention. AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do NOT use solvents or thinners. AFTER EYE CONTACT: Keep eye wide open while rinsing. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. If symptoms persist, call a physician or Poison Control Centre immediately. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye damage. May cause damage to organs through prolonged or repeated exposure. Harmful by inhalation. Irritating to skin. May cause birth defects.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Explosive reaction may occur on heating or burning. In use, may form flammable/explosive vapour-air mixture.

5.3 Advice for firefighters

Keep containers and surroundings cool with water spray. Fire will produce dense black smoke containing hazardous combustion products (see section 10). Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Ventilate the area. Refer to protective measures listed in sections 7 and 8.

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. As a rule, at least 10 air changes per hour are recommended at the workplace. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feeding stuffs. When using, do not eat, drink or smoke. Wash hands and face before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Heat, flames and sparks. Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Store at room temperature in the original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	CAS-No.	<u>LTEL ppm</u>	STEL ppm	STEL mg/m3	LTEL mg/m3
Styrene	100-42-5	100	250	1080	430

Name CAS-No. OEL Note

Styrene 100-42-5

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In case of insufficient ventilation wear suitable respiratory equipment, filter A.

EYE PROTECTION: Tightly fitting safety goggles. Safety glasses with side-shields conforming to EN 166.

HAND PROTECTION: Use chemical resistant gloves (EN 374): Nitrile rubber; thickness >=0,5 mm; breakthrough time >= 480 min. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Protective suit. Remove contaminated clothing and protective equipment before entering eating areas.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: As a rule, at least 10 air changes per hour are recommended at the workplace. Avoid contact with skin, eyes and clothing. Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Chemical Name:

Styrene

EC No.: CAS-No.: 202-851-5 100-42-5

DNELs - Derived no effect level

	Workers		Consumers					
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not	required	<u> </u>				
Inhalation	306 mg/m ³	289 mg/m ³		85 mg/m³				
Dermal				406 mg/kg bw/				
	_			day				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.028 mg/L
Fresh water sediments	0.614 mg/kg
Marine water	0.014 mg/L
Marine sediments	0.307 mg/kg
Food chain	None
Microorganisms in sewage treatment	5 mg/L soil dw
soil (agricultural)	0.2 mg/kg
Air	None

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties	9.1	Information on	basic phy	sical and	chemical	propertie
---	-----	----------------	-----------	-----------	----------	-----------

Appearance: Various colors

Physical State Liquid

Odor characteristic

Odor threshold Not determined

pH Not determined

Melting point / freezing point (°C) Not determined

Boiling point/range (°C) 145 - N.D.

Flash Point, (°C) ~31

Evaporation rate Not determined

Flammability (solid, gas) Not applicable

Upper/lower flammability or explosive

limits

999 - -999

Vapour Pressure Not determined

Vapour density Not determined

Relative density 1.04 g/ml (20°C)

Solubility in / Miscibility with water Not determined

Partition coefficient: n-octanol/water

Not determined

Not determined

Auto-ignition temperature (°C)

Decomposition temperature (°C)

Not determined

Viscosity

Not determined

Explosive properties

Not determined

9.2 Other information

Oxidising properties

VOC Content g/l: 470

This is a calculated maximum VOC content for the mixed ready to use product (to Directive 2004/42/EC).

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Polymerisation occurs when exposed to white light, ultraviolet light or heat.

10.4 Conditions to avoid

Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Heat, flames and sparks. Direct sources of heat.

10.5 Incompatible materials

Oxidizing agents. Strong oxidizing agents. Amines. Reducing agents. Heavy metal salts. Avoid radical-forming starting agents, peroxides and reactive metals.

10.6 Hazardous decomposition products

In case of fire **hazardous decomposition products** may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). No dangerous reaction known under conditions of normal use.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available on the product itself as the product is not tested.

Inhalation LC50: No information available on the product itself as the product is not tested.

Irritation: Causes serious eye irritation.

Corrosivity: Not corrosive.

Sensitization: Not expected to be sensitising.

Repeated dose toxicity: None Known

Carcinogenicity: Not carcinogenic.

Mutagenicity: None Known

Toxicity for reproduction: Reproductive Toxicity, category 2

STOT-single exposure: STOT, single exposure, category 3, RTI

STOT-repeated exposure: STOT, repeated exposure, category 1

Aspiration hazard: None Known

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

 CAS-No.
 Name According to EEC
 Oral LD50
 Dermal LD50
 Vapor LC50
 Gas LC50
 Dust/Mist LC50

 100-42-5
 Styrene
 5000 mg/kg (rat)
 2001 mg/kg (rat)
 12 mg/l (rat)
 2770 ppm
 1.5 mg/l (rat)

Additional Information: Harmful if inhaled.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

No information available on the product itself as the product is not tested.

No information available on the product itself as the product is not tested.

LC50 96hr (fish):

No information available on the product itself as the product is not tested.

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: None

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

 CAS-No.
 Name According to EEC
 EC50 48hr
 IC50 72hr
 LC50 96hr

 100-42-5
 Styrene
 4.7 mg/l
 4.8 mg/l
 4.02 mg/l

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Container hazardous when empty. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 080111*
Packaging Waste Code: 150110

SECTION 14: Transport Information

14.1 UN number UN126314.2 UN proper shipping name Paint

Technical name Not applicable

14.3 Transport hazard class(es)

Subsidiary shipping hazard Not applicable

14.4 Packing group III14.5 Environmental hazards No

14.6 Special precautions for user Not applicable EmS-No.: F-E, S-E

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

Germany WGK Class: Not available

Directive 2004/42/CE : 470

Covered by Directive 2012/18/EC (Seveso III): P5c

Restrictions to product or to substances according

to Annex XVII, Regulation (CE) 1907/2006: Not applicable

Annex XIV - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List):

CAS-No. Name According to EEC

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

Reasons for revision

Composition Information Changed Substance Hazard Threshold % Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

08 - Exposure Controls/Personal Protection

09 - Physical and Chemical Properties

11 - Toxicological Information
12 - Ecological Information
14 - Transportation Information
15 - Regulatory Information
Substance CAS Number Changed

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.