

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### · 1.1 Product identifier

· Trade name: Nullifire SC900 A

· MSDS code: W-N-SC900A

### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· **Application of the substance / the mixture** Coating compound/ Surface coating/ paint

### · 1.3 Details of the supplier of the safety data sheet

#### · Manufacturer/Supplier:

Tremco CPG UK Ltd

Coupland Road, Hindley Green, WIGAN, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@cpg-europe.com

#### · Further information obtainable from:

See above-mentioned address

Tremco CPG UK Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.cpg-europe.com, info.uk@cpg-europe.com

### · 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

## SECTION 2: Hazards identification

### · 2.1 Classification of the substance or mixture

#### · Classification according to Regulation (EC) No 1272/2008

Repr. 2 H361f Suspected of damaging fertility.

· **Additional information:** (EC) 1272/2008 'CLP' & GB-CLP: 2.6.4.5 (Flam. Liq. 3)

### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### · Hazard pictograms



GHS08

· **Signal word** Warning

(Contd. on page 2)

# Safety data sheet

acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 13.07.2021

Version number 10

Revision: 10.06.2021

**Trade name: Nullifire SC900 A**

(Contd. of page 1)

- **Contains:**

melamine

- **Hazard statements**

H361f Suspected of damaging fertility.

- **Precautionary statements**

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 Wear respiratory protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

- **Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC**

VOC 2004/42/CE &amp; UK SI 2012/1715 (A / j) = &lt;500 g/l

Nullifire SC900 A

= 139 g/l

- **2.3 Other hazards** No further relevant information available.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with non-hazardous additions.

- **Dangerous components:**

CAS: 108-78-1 EINECS: 203-615-4 Reg.nr.: 01-2119485947-16-xxxx	melamine Repr. 2, H361f	10-<20%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	5-<10%
CAS: 28553-12-0 EINECS: 249-079-5 Reg.nr.: 01-2119430798-28-xxxx	1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (DINP; di-"isononyl" phthalate) substance with a Community workplace exposure limit	1-<5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	1-<5%
CAS: 64741-65-7 EINECS: 265-067-2 Reg.nr.: 01-2119471991-29-xxxx	Naphtha (petroleum), heavy alkylate Flam. Liq. 3, H226; Acute Tox. 3, H331; Asp. Tox. 1, H304; Aquatic Chronic 2, H411	0.1-<1%

- **SVHC -**

(Contd. on page 3)

**Trade name: Nullifire SC900 A**

(Contd. of page 2)

· **Additional information:**

For the wording of the listed hazard phrases refer to section 16.

Fillers are encapsulated within the liquid and therefore not expected to be released from the product under normal conditions of use.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **General information:** Take affected persons out of danger area and lay down.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· **Information for doctor:** No further relevant information available.

· **4.2 Most important symptoms and effects, both acute and delayed** Suspected of damaging fertility.

· **Hazards** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

**SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

(Contd. on page 4)

**Trade name: Nullifire SC900 A**

(Contd. of page 3)

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### Information about fire - and explosion protection:

Flammable liquid and vapour.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Provide ventilation for receptacles.

#### Information about storage in one common storage facility: Protect from heat and direct sunlight.

#### Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Storage temperature: 0°C to +35°C

### 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

##### CAS: 1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm

Long-term value: 220 mg/m<sup>3</sup>, 50 ppm

Sk; BMGV

##### CAS: 28553-12-0 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (DINP; di-"isononyl" phthalate)

WEL Long-term value: 5 mg/m<sup>3</sup>

##### CAS: 100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m<sup>3</sup>, 125 ppm

Long-term value: 441 mg/m<sup>3</sup>, 100 ppm

Sk

#### DNELs

##### CAS: 108-78-1 melamine

Inhalative	DNEL	8.3 mg/m <sup>3</sup> (workers) (systemic effects)
------------	------	----------------------------------------------------

(Contd. on page 5)

**Trade name: Nullifire SC900 A**

(Contd. of page 4)

· **Ingredients with biological limit values:**

**CAS: 1330-20-7 xylene (mix)**

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	----------------------------------------------------------------------------------------------------------

· **Additional Occupational Exposure Limit Values for possible hazards during processing:**

Fillers are encapsulated within the liquid and therefore not expected to be released from the product under normal conditions of use.

· **Additional information:**

The lists valid during the making were used as basis.  
HSE EH40/2005 Workplace Exposure Limits (as amended)

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Ensure good ventilation/exhaustion at the workplace.

Do not breathe spray.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Wear respiratory protection.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Filter A/P2

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

PVA gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

**Trade name: Nullifire SC900 A**

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Viscous

Colour: White

· **Odour:** Characteristic

· **pH-value:**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 137-143 °C

· **Flash point:** 46 °C

· **Ignition temperature:** 500 °C

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Density at 20 °C:** 1.55 g/cm<sup>3</sup>

· **Solubility in / Miscibility with water:** Immiscible / difficult to mix.

· **Solvent content:**

VOC (EU) 139.0 g/l

VOC (EC) 139 g/l

8.96 %

· **9.2 Other information** No further relevant information available.

# Safety data sheet

acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 13.07.2021

Version number 10

Revision: 10.06.2021

Trade name: Nullifire SC900 A

(Contd. of page 6)

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** Stable
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid**  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Nitrogen oxides  
Carbon monoxide and carbon dioxide

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

### · LD/LC50 values relevant for classification:

#### CAS: 108-78-1 melamine

Oral	LD50	3,161 mg/kg (rat)
------	------	-------------------

#### CAS: 1330-20-7 xylene (mix)

Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	27.124 mg/L (rat)
	LC50/4 h	5,000 ppmV (rat)

#### CAS: 100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)

#### CAS: 64741-65-7 Naphtha (petroleum), heavy alkylate

Oral	LD50	>6,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>7.8 mg/L (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Slight irritation possible.
- **Serious eye damage/irritation** Slight irritation possible.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**  
Repeated exposure may cause skin dryness or cracking.  
Fillers are encapsulated within the liquid and therefore not expected to be released from the product under normal conditions of use.  
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(Contd. on page 8)

# Safety data sheet

acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 13.07.2021

Version number 10

Revision: 10.06.2021

Trade name: Nullifire SC900 A

(Contd. of page 7)

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
Suspected of damaging fertility.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

##### CAS: 1330-20-7 xylene (mix)

LC50/96 h | 4.2 mg/L (rainbow trout)

EC50/48 h | 2.93-4.4 mg/L (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

#### Ecotoxicological effects:

##### CAS: 1330-20-7 xylene (mix)

IC50/72 h | 2.2 mg/L (algae)

#### Additional ecological information:

#### General notes:

Overall evaluation

Avoid transfer into the environment.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

#### European waste catalogue

08 01 11\* | waste paint and varnish containing organic solvents or other hazardous substances

HP10 | Toxic for reproduction

(Contd. on page 9)

## Safety data sheet

acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 13.07.2021

Version number 10

Revision: 10.06.2021

Trade name: Nullifire SC900 A

(Contd. of page 8)

- **Uncleaned packaging:**
- **Recommendation:**  
Disposal must be made according to official regulations.  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.  
Non contaminated packagings may be recycled.

### SECTION 14: Transport information

· <b>14.1 UN-Number</b>	
· <b>ADR, ADN, IMDG, IATA</b>	Void
· <b>14.2 UN proper shipping name</b>	
· <b>ADR</b>	Void
	Void
· <b>ADN, IMDG, IATA</b>	Void
· <b>14.3 Transport hazard class(es)</b>	
· <b>ADR, ADN, IMDG, IATA</b>	
· <b>Class</b>	Void
· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Not applicable.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	2.2.3.1.1 (note 1)
· <b>IMDG</b>	2.3.1.3
· <b>IATA</b>	3.3.1.3
· <b>UN "Model Regulation":</b>	Void

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).  
"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).  
COMMISSION REGULATION (EU) 2020/878 of 18 June 2020.  
HSE EH40/2005 Workplace Exposure Limits (as amended)

(Contd. on page 10)

GB

# Safety data sheet

acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 13.07.2021

Version number 10

Revision: 10.06.2021

**Trade name: Nullifire SC900 A**

(Contd. of page 9)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)  
 STATUTORY INSTRUMENTS 2012 No. 1715 ENVIRONMENTAL PROTECTION | The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012, and any subsequent amendments

- **National regulations:**
- **Information about limitation of use:**  
 Employment restrictions concerning juveniles must be observed.  
 Employment restrictions concerning pregnant and lactating women must be observed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
 H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H312 Harmful in contact with skin.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.  
 H361f Suspected of damaging fertility.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.
- **Department issuing SDS:**  
 Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.
- **Abbreviations and acronyms:**  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 DNEL: Derived No-Effect Level (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 SVHC: Substances of Very High Concern  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 11)

**Safety data sheet**  
acc. to (EC) No 1907/2006, as amended by UK SI 2019/758

Printing date 13.07.2021

Version number 10

Revision: 10.06.2021

**Trade name: Nullifire SC900 A**

(Contd. of page 10)

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered.**